

GNT-P9206EB

GNT-P9206EB 4p 2Up-Link 130m AI PoE Switch Genata



Model	GNT-P9206EB
Brend	Genata
PoE gücü	60 W
Port sayı	5 Port
PoE	PoE
Port sürati	100mb/s

Specification

Ports	<p>PoE (1~3) :10/100Mbps PoE ports (RJ45)</p> <p>PoE (4) :10/100Mbps PoE port,BT port, Compatible uplink port (RJ45)</p> <p>LAN (1~2):10/100Mbps uplink port (RJ45)</p>
Transmission Rate	200Mbps Full Duplex; 10 or 100 Mbps Half Duplex
Transmission Distance	100Mbps /10Mbps Adaptive MAX 250m
Performance Specification	<p>Bandwidth: 1.2Gbps</p> <p>Network Latency (10 to 1000Mbps): 16µs (use the 64byte package size)</p> <p>MAC address table: 2K</p> <p>The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port</p>
Networking Standard	<p>IEEE 802.3i 10BASE-T</p> <p>IEEE 802.3u 100BASE-TX</p> <p>IEEE 802.3xFlowControl</p> <p>IEEE 802.3af/at/bt Power over Ethernet</p>
Power Support	<p>Power input: AC 110~220V Totals≤65W</p> <p>PoE Watchdog: Port 1~4</p> <p>Power output: PoE1~3Port:1/2(+52V),3/6(GND)≤30W</p> <p>PoE 4 Port:1245(+53V),3678(GND) compatible1/2(+52V),3/6(GND)≤60W</p>

Protection Level	Lightning Protection:6KV, Per: IEC61000-4-5 ESD Protection:8KV, Per: IEC61000-4-2
Package Size	Size(L*W*H):187mm*139mm*43mm
Working Environment	Operating Temperature: -30~60 Storage Temperature: -40~70 Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Electromagnetic Compatibility	CE mark FCCPart15,Class B VCCI ClassBEN55022 (CISPR 22) C-Tick
Warranty	Whole device: 1 year
Package Content	Installation Manual