eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

GENATA

GNT-P9828V6

Kod: 00-00004890 · Switchlər



GNT-P9828V6 8p 2Up-Link 250m AI Hybrid PoE Switch Genata

Texniki göstəricilər

8 Port
Port sayı

PoE
PoE

100mb/s
Port sürəti

120 W
PoE gücü

Ətraflı məlumat

DATA SHEET	
Port	2*100Mbps Uplink ports +8*100Mbps PoE ports
Transmission Rate	2000Mbps Full Duplex; 10 or 100 or 1000Mbps Half Duplex
Max transmission distance	130m
Power support	Power input: AC 110~220V Total≤120W PoE Watchdog: Port 1-8 Power output: PoE1~6Port:1/2(+52V),3/6(GND)≤30W PoE7~8Port:1245(+53V),3678(GND) compatible1/2(+52V),3/6(GND)≤60W
Ports(1-6)Support	IEEE 802.3af/at protocol
Ports(7-8)Support	IEEE 802.3af/at/bt protocol
Performance Specification	Bandwidth: 2 Gbps
	Network Latency (10 to 1000Mbps): ≦16μs (use the 64byte package size)
	MAC address table: 2K
	The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port,1488000pps the most for 1000M port
Networking Standard	IEEE 802.3i 10BASE-T
	IEEE 802.3u 100BASE-TX/ IEEE 802.3ab 1000BASE-T
	IEEE 802.3xFlowControl
	IEEE 802.3af/at/bt Power over Ethernet
Protection Level	Lightning Protection:6KV, Per: IEC61000-4-5 ESD Protection:8KV, Per: IEC61000-4-2
Physical Specifications	Size(L*W*H)： 187mm*139mm*43mm
Working Environment	Operating Temperature: -30℃ ~60℃
	Storage Temperature: -40℃ ~70℃

Operating Humidity: 10%~90% non-condensing	
Storage Humidity: 5%~90% non-condensing	
Electromagnetic Compatibility	CE mark
	FCC Part15 Class B
	VCCI Class BEN55022 (CISPR 22)
	C-Tick
Other Functions	Short-circuit protection
	Over-Temperature protection
	Preventing surge
Package Content	AC Power Cable Installation Manual

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az