eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

GENATA

GNT-RP1428ES

Kod: 00-00004891 · Switchlər



GNT-RP1428ES 24p 2Up-Link 2SFP 250m AI PoE Switch Genata

Texniki göstəricilər

24 Port
Port sayı

PoE
PoE

100mb/s
Port sürəti

300 W
PoE gücü

Ətraflı məlumat

Model	GNT-RP1428ES
Ports	PoE (1~22):10/100Mbps PoE ports (RJ45) PoE (23~24):10/100Mbps PoE ports,Support bt 60W High Power LAN(25~26):10/100/1000Mbps uplink ports (RJ45) SFP(27~28):10/100/1000Mbps SFP port
Transmission Rate	2000Mbps FullDuplex; 10 or 100 or 1000 MbpsHalf Duplex
Transmission Distance	100Mbps /10Mbps,Auto-Adaption 250m
Performance Specification	Bandwidth:12.8Gbps
	Network Latency(10 to 1000Mbps): ≦16μs (use the 64bytepackage size)
	MAC address table: 8K
	The FrameFilter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port;1488000pps the most for 1000M port
Networking Standard	IEEE 802.3i 10BASE-T/IEEE 802.3u100BASE-TX
	IEEE 802.3ab 1000BASE-T
	IEEE 802.3x Flow Control
	IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power Input:AC 90~240V Total≤300W AI Watchdog: Port 1~24 Power Output:PoE1~22 Port:1/2(+52V),3/6(GND)≤30W PoE23~24 Port:1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Lightning Protection:6KV ESD Protection:8KV
Physical Specifications	Size(L*W*H): 440mm*180mm*45mm, Weight:2.65KG
Working Environment	Operating Temperature: -30°C~60°C
	Storage Temperature: -40°C~70°C
	Operating Humidity: 10%~90% Non-condensing

Storage Humidity: 5%~90% Non-condensing	
Certification	CE Mark
	FCC Part15,Class B
	RoHS 2.0
Package Content	AC Power Cable,User Manual

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az