

GNT-RP1428ES

GNT-RP1428ES 24p 2Up-Link 2SFP 250m AI PoE Switch Genata



Model	GNT-RP1428ES
Brend	Genata
PoE gücü	300 W
Port sayı	24 Port
PoE	PoE
Port sürati	100mb/s

Specification

Model	GNT-RP1428ES
Ports	<p>PoE (1~22):10/100Mbps PoE ports (RJ45)</p> <p>PoE (23~24):10/100Mbps PoE ports,Support bt 60W High Power</p> <p>LAN(25~26):10/100/1000Mbps uplink ports (RJ45) SFP(27~28):10/100/1000Mbps SFP port</p>
Transmission Rate	2000Mbps FullDuplex; 10 or 100 or 1000 MbpsHalf Duplex
Transmission Distance	100Mbps /10Mbps,Auto-Adaption 250m
Performance Specification	<p>Bandwidth:12.8Gbps</p> <p>Network Latency(10 to 1000Mbps): 16µs (use the 64bytepackage size)</p> <p>MAC address table: 8K</p> <p>The FrameFilter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port;1488000pps the most for 1000M port</p>
Networking Standard	<p>IEEE 802.3i 10BASE-T/IEEE 802.3u100BASE-TX</p> <p>IEEE 802.3ab 1000BASE-T</p> <p>IEEE 802.3x Flow Control</p> <p>IEEE 802.3af/at/bt Power over Ethernet</p>

Power Support	Power Input: AC 90~240V Totals300W AI Watchdog: Port 1~24 Power Output: PoE1~22 Port:1/2(+52V),3/6(GND)≤30W PoE23~24 Port: 1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Lightning Protection: 6KV ESD Protection: 8KV
Physical Specifications	Size(L*W*H): 440mm*180mm*45mm, Weight: 2.65KG
Working Environment	Operating Temperature: -30°C~60°C
	Storage Temperature: -40°C~70°C
	Operating Humidity: 10%~90% Non-condensing
	Storage Humidity: 5%~90% Non-condensing
Certification	CE Mark
	FCC Part15,Class B
	RoHS 2.0
Package Content	AC Power Cable,User Manual