

# GS1005PTS1

CUDY GS1005PTS1 5-Port Gigabit PoE+ Switch with 1 SFP Slot



Model	GS1005PTS1
Brend	Cudy
Port sayı	5 Port
PoE	PoE+
PoE gücü	60 W
Port sürati	1000mb/s

## Specification

Model	GS1005PTS1
Ethernet	4*10/100/1000M PoE Port 1*1000M RJ45 Port 1* Gigabit SFP Uplink Port
Switching Capacity	12Gbps
Throughput	8.928Mpps
Packet Buffer	1Mb
MAC Address	2K
Jumbo Frame	9216bytes
Transfer Mode	Store and forward
MTBF	100000 hour
Network protocol	IEEE802.3 (10Base-T) IEEE802.3u (100Base-TX) IEEE802.3ab(1000Base-TX) IEEE802.3z(1000Base-FX) IEEE802.3x (Flow control)
PoE Protocol	IEEE802.3af    15.4W   IEEE802.3at    30W   IEEE802.3at    4 Pair 60W
Network Medium	10Base-T : Cat3  4  5 or above UTP(≤100m) 100Base-TX : Cat5 or above UTP(≤100m) 1000Base-TX : Cat5 or above UTP(≤100m)

Optical Media	Multimode fiber : 50/125, 62.5/125, 100/140µm Single mode fiber: 8/125, 8.7/125, 9/125, 10/125µm
Working Environment	Working Temperature:-20~50°C Storage Temperature:-40~85°C Working Humidity :10%~90%non-condensing Storage Temperature:5%~90%non-condensing Working Height:Maximum10,000 feet Storage heigh:Maximum 10,000 feet
PWR:power supply:	Lighting:Powered Un-Light:No Power
Mode:DIP:	Lighting:VLAN Un-Light:Default Flashing:Extend
1-6 Gree:Link&Data:	Lighting:Connecting Flashing:Data Transmit Un-Light:Disconnect
DIP Switch	VLAN:Port isolation mode. In this mode, the PoE ports (1-4) of the switch cannot communicate with each other, and can only communicate with the UP-link port. Default: Normal mode, all port can communicate with each other, the transmission distance is within 100 meters Extend:Link extension mode, 3-4 ports PoE power supply and data transmission distance can be extended to 250 meters, the transmission rate becomes 10M
Product Dimension	200*118*44mm
Package Dimension	245*190*60mm
N.W	0.6kg
G.W	0.9kg
Packing Info	Carton MEAS:505*320*402mm Packing Qty:20units Packing Weight:19KG
Package List	Input Voltage :AC 100-240 V
Package List	Switch 1 pcs, Power cord 1 pcs, User manual 1 pc, Certification 1 pc,