

GS1005PTS1

CUDY GS1005PTS1 5-Port Gigabit PoE+ Switch with 1 SFP Slot



Model	GS1005PTS1
Brend	Cudy
Port sayı	5 Port
PoE	PoE+
PoE gücü	60 W
Port sürəti	1000mb/s

Specification

Model	GS1005PTS1
Ethernet	4*10/100/1000M PoE Port 1*1000M RJ45 Port 1* Gigabit SFP Uplink Port
Switching Capacity	12Gbps
Throughput	8.928Mpps
Packet Buffer	1Mb
MAC Address	2K
Jumbo Frame	9216bytes
Transfer Mode	Store and forward
MTBF	100000 hour
Network protocol	IEEE802.3 (10Base-T) IEEE802.3u (100Base-TX) IEEE802.3ab(1000Base-TX) IEEE802.3z(1000Base-FX) IEEE802.3x (Flow control)

PoE Protocol	IEEE802.3af @15.4W IEEE802.3at @30W IEEE802.3at @4 Pair 60W
Network Medium	10Base-T : Cat3@4@5 or above UTP(≤100m) 100Base-TX : Cat5 or above UTP(≤100m) 1000Base-TX : Cat5 or above UTP(≤100m)
Optical Media	Multimode fiber : 50/125, 62.5/125, 100/140μm Single mode fiber: 8/125, 8.7/125, 9/125, 10/125μm
Working Environment	Working Temperature:-20~50°C Storage Temperature:-40~85°C Working Humidity @10%~90%non-condensing Storage Temperature@5%~90%non-condensing Working Height@Maximum10,000 feet Storage height@Maximum 10,000 feet
PWR@power supply@	Lighting@Powered Un-Light@No Power
Mode@DIP@	Lighting@VLAN Un-Light@Default Flashing@Extend
1-6 Gree@Link&Data@	Lighting@Connecting Flashing@Data Transmit Un-Light@Disconnect
DIP Switch	VLAN@Port isolation mode. In this mode, the PoE ports (1-4) of the switch cannot communicate with each other, and can only communicate with the UP-link port. Default: Normal mode, all port can communicate with each other, the transmission distance is within 100 meters Extend@Link extension mode, 3-4 ports PoE power supply and data transmission distance can be extended to 250 meters, the transmission rate becomes 10M
Product Dimension	200*118*44mm
Package Dimension	245*190*60mm
N.W	0.6kg
G.W	0.9kg
Packing Info	Carton MEAS@505*320*402mm Packing Qty@20units Packing Weight@19KG
Package List	Input Voltage @AC 100-240 V
Package List	Switch 1 pcs, Power cord 1 pcs, User manual 1 pc, Certification 1 pc,