

GS1010P

CUDY GS1010P 8-Port Gigabit PoE+ Switch with 2 Gigabit Uplink ports 120w



Specifications

Model	GS1010P
Brand	Cudy
Port say?	8 Port
PoE	PoE+
PoE gücü	120 W
Port sür?ti	1000mb/s

KEY FEATURES

Model	GS1010P
PoE standard	IEEE802.3af/at
Interface	10*10/100/1000Mbps The RJ45 port through consultationa
Key function	CCTV&VLAN
PoE port	1~8 port
PoE Total	120W
Power supply	120W
RJ45 PoE power supply	Mode A Anode1/2 Cathode3/6
PoE output-port	Max 32W
Indicator	PWR, LNK/ACT, PoE
Network media	10BASE-T: UTP category 3, 4, 5 cable(≤100m) 100BASE-TX: UTP category 5, 5e cable(≤100m) 1000BASE-T: UTP category 5e,6 cable(≤100m)
MAC Address Table	8K, Automatic study, automatic updates
Jumbo frame	9216Bytes
Packet buffer	2M bit
Transfer Mode	Store-and-forward
Packet forwarding rate	13.4Mpps
Bandwidth	18 Gbps
Fan	Fanless
Device Dimension	200*118*44mm
Machine Weight	>1kg
Green energy saving	Support IEEE 802.3az)
Mains Input	100~240V AC 50/60Hz
Operating Temperature	0°C ~ 40 °C
Storage Temperature	-40 °C ~ 70 °C
Operating Humidity	10% ~ 90% non-condensing
Storage Humidity	5% ~ 90% non-condensing
Surge Protection	±4KV
MTBF	>50000 hour
Electrostatic standard	Contact 6KV, air 8KV