

CUDY**GS1016L**

Kod: 00-00005578 · Switchlər



CUDY GS1016L 16-Port Gigabit Metal Switch genişlənmiş şəbəkələr üçün yüksək sürətli və dayanıqlı bağlantı təqdim edir. Plug & Play dəstəyi, metal korpusu və səssiz işləmə xüsusiyyəti ilə ofis, mağaza və kiçik biznes mühitləri üçün ideal seçimdir.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](#)<https://eurotechnology.az/product/cudy/gs1016l>**Texniki göstəricilər****16 Port**

Port sayı

**1000mb/s**

Port sürəti

Ətraflı məlumat

Model	GS1016L 1.0
Gigabit RJ45 Ports	16
Shielded RJ45 Port	True
Extend Mode Ports	#1~#14
VLAN Mode Ports	#1~#14
LED	• Power • Speed/Link/Act of Each Ethernet Port
Power Interfaces	AC Inlet
Physical Buttons	VLAN/Default/Extend DIP Switch
Copper Speed and Distance	• Cat. 3 or higher cable: 100 meters at 10 Mbps • Cat. 5 or higher cable: 100 meters at 100 Mbps • Cat. 5e or higher cable: 100 meters at Gigabit • Cat. 5e or higher cable: 250 meters at 10 Mbps
Copper Speed and Distance Note	250-meter transmission is only available on the Extend Mode ports when the Extend Mode is activated.
MAC Address Table	8192
Max Switching Capacity	32 Gbps
Max Forwarding Rate	23.808 Mpps
Jumbo Frame	15 KB
Packet Buffer	4 Mbit
Basic Power Saving	True
Power Methods	AC
Power Input	90-260V~ 50/60Hz
Max Power Consumption	7.8W
Idle Power Consumption	4.5W

802.3 Protocols	• 802.3x Flow Control • 802.3i 10BASE-T • 802.3u 100BASE-TX • 802.3ab 1000BASE-T
802.1 Protocols	802.1p: LAN Layer 2 QoS/CoS
L2 Features	• IGMP Snooping • Loop Prevention • Loop Detection • DSCP QoS • 802.1p QoS
Grounding Methods	• Three-Prong Plug • Grounding Point
EMS	IEC/EN 61000-4-2, Level 3 ESD: Contact: 6kV; Air: 8kV IEC/EN 61000-4-5, Level 4 Surge: Power: DM 2kV, CM 4kV; RJ45: CM 4kV
Environment	Operating Temperature: 0 °C ~ 40 °C (32 °F ~ 104 °F) Storage Temperature: -40 °C ~ 70 °C (-40 °F ~ 158 °F) Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5% ~ 90% non-condensing
Dimension	440×180×44 mm 17.32×7.09×1.73 inches
Product Weight	1597.9 g (56.36 oz.)
Casing Material	Metal
Installation	• Desktop • Rackmount via Brackets
• GS1016L • Power Cord • Installation Guide • Mounting Kit	
Retail Package Dimension	487×267×84 mm 19.17×10.51×3.31 inches
Retail Package Weight	EU: 2278.4 g (80.37 oz.)

Units per Carton	5
Carton Net Weight	EU: 11.4 kg (25.13 lbs)
Carton Gross Weight	EU: 12.3 kg (27.12 lbs)
Carton Dimension	50×44×28.5 cm 19.69×17.32×11.22 inches

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az