

CUDY**GS1024L**

Kod: 00-00005583 · Switchlər



CUDY GS1024L 24-Port Gigabit Metal Switch stabil və sürətli şəbəkə bağlantısı üçün nəzərdə tutulub. 24 ədəd gigabit port eyni anda çoxsaylı cihazların problemsiz işləməsini təmin edir. Metal korpus uzunömürlü istifadə və effektiv istilik yayılması yaradır. Ofis, mağaza və SMB mühitləri üçün etibarlı seçimdir.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](https://eurotechnology.az/product/cudy/gs1024l)
<https://eurotechnology.az/product/cudy/gs1024l>

Texniki göstəricilər**24 Port**

Port sayı

**1000mb/s**

Port sürəti

Ətraflı məlumat

Model	GS1024L 1.0
Gigabit RJ45 Ports	24
Shielded RJ45 Port	True
Extend Mode Ports	#1~#22
VLAN Mode Ports	#1~#22
LED	• Power • Speed/Link/Act of Each Ethernet Port
Power Interfaces	AC Inlet
Physical Buttons	VLAN/Default/Extend DIP Switch
Copper Speed and Distance	• Cat. 3 or higher cable: 100 meters at 10 Mbps • Cat. 5 or higher cable: 100 meters at 100 Mbps • Cat. 5e or higher cable: 100 meters at Gigabit • Cat. 5e or higher cable: 250 meters at 10 Mbps
Copper Speed and Distance Note	250-meter transmission is only available on the Extend Mode ports when the Extend Mode is activated.
MAC Address Table	8192
Max Switching Capacity	48 Gbps
Max Forwarding Rate	35.712 Mpps
Jumbo Frame	15 KB
Packet Buffer	4 Mbit
Basic Power Saving	True
Power Methods	AC
Power Input	90-260V~ 50/60Hz
Max Power Consumption	11W
Idle Power Consumption	6.8W

802.3 Protocols	• 802.3x Flow Control • 802.3i 10BASE-T • 802.3u 100BASE-TX • 802.3ab 1000BASE-T
802.1 Protocols	802.1p: LAN Layer 2 QoS/CoS
L2 Features	• IGMP Snooping • Loop Prevention • Loop Detection • DSCP QoS • 802.1p QoS
Grounding Methods	• Three-Prong Plug • Grounding Point
EMS	IEC/EN 61000-4-2, Level 3 ESD: Contact: 6kV; Air: 8kV IEC/EN 61000-4-5, Level 4 Surge: Power: DM 2kV, CM 4kV; RJ45: CM 4kV
Environment	Operating Temperature: 0 °C ~ 40 °C (32 °F ~ 104 °F) Storage Temperature: -40 °C ~ 70 °C (-40 °F ~ 158 °F) Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5% ~ 90% non-condensing
Dimension	440×180×44 mm 17.32×7.09×1.73 inches
Product Weight	EU / US: 1671 g (58.94 oz.),EU: 1650 g (58.2 oz.)
Casing Material	Metal
Installation	• Desktop • Rackmount via Brackets
• GS1024L • Power Cord • Installation Guide • Mounting Kit	
Retail Package Dimension	487×267×84 mm 19.17×10.51×3.31 inches

Retail Package Weight	• EU / US: 2380 g (83.95 oz.) • EU: 2300 g (81.13 oz.)
Units per Carton	5
Carton Net Weight	• EU / US: 11.9 kg (26.23 lbs) • EU: 11.5 kg (25.35 lbs)
Carton Gross Weight	• EU / US: 12.9 kg (28.44 lbs) • EU: 13.0 kg (28.66 lbs)
Carton Dimension	50×44×28.5 cm 19.69×17.32×11.22 inches

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az