

GS1026PS2

CUDY GS1026PS2 24-Port Gigabit PoE+ Switch with 2 Uplink Gigabit Ports and 2 Gigabit SFP Slots 300W, 24× GbE with 802.3at/af PoE, 2× Uplink GbE + 2× Uplink SFP, 300W Power Supply, Default/Extend Modes, Watchdog under Extend Mode, Desktop, Rack-Mount, 320×207×44 mm (12.6×8.15×1.73")



Specifications

Model	GS1026PS2
Brand	Cudy
PoE gücü	300 W
Port say?	24 Port
Port sür?ti	1000mb/s
PoE	PoE+

KEY FEATURES

GS1026PS2 1.0

Gigabit SFP Slots 2

Gigabit RJ45 Ports 2

Gigabit RJ45 PoE Ports 24

Max Power on a Single PoE Port 30W

PoE Port Notes PoE ports are 802.3at/af compatible.

Extend Mode Ports #17~#24

LED

- Power
- DIP Mode (SW)
- PoE Status of Each PoE Port
- Link/ACT of Each Ethernet Port
- PoE Max Status

Power Input AC Inlet

Physical Buttons

- Default/Extend DIP switch
- PoE LED Toggle

Physical Buttons Note

The PoE Watchdog is on under the Extend mode and will attempt to reboot the plugged-in but inactive client.

Copper Speed and Distance

- Cat. 3 or higher cable: 100 meters at 10 Mbps
- Cat. 5 or higher cable: 100 meters at 100 Mbps
- Cat. 5e or higher cable: 100 meters at Gigabit
- Cat. 5e or higher cable: 250 meters at 10 Mbps

Copper Speed and Distance Note 250-meter transmission is only available on the Extend Mode ports.

Optical Spec and Distance Depends on the Installed Optical Module

MAC Address Table 8192

Max Switching Capacity 56 Gbps

Max Forwarding Rate 41.664 Mpps

Packet Buffer 3 Mbit

Power Methods AC

AC 100-240V 50/60Hz

Power Supply 300W

Max Power Excluding PoE 20W

802.3 Protocols

- 802.3i 10BASE-T
- 802.3u 100BASE-TX
- 802.3ab 1000BASE-T
- 802.3z 1000BASE-X
- 802.3x Flow Control
- 802.3af PoE
- 802.3at PoE

Grounding Methods Three-Prong Plug

Lightning/Surge Protection Power: DM 2kV, CM 4kV

Environment	Operating Temperature: 0~40 ℃ (32~104 ℉) Storage Temperature: -40~70 ℃ (-40~158 ℉) Operating Humidity: 10~90% non-condensing Storage Humidity: 10~95% non-condensing
Dimension	320×207×44 mm 12.6×8.15×1.73 inches
Product Weight	1986 g (70.05 oz.)
Casing Material	Metal
Installation	<ul style="list-style-type: none">• Desktop• Rackmount via Brackets
	<ul style="list-style-type: none">• GS1026PS2• Power Cord• Mounting Kit• Installation Guide
Retail Package Dimension	370×290×85 mm 14.57×11.42×3.35 inches
Retail Package Weight	EU: 2534 g (89.38 oz.)
Carton Net Weight	EU: 12.7 kg (28 lbs)
Carton Gross Weight	EU: 13.6 kg (29.98 lbs)