CUDY

GS1026PS2

Kod: 00-00004797 · Switchlər



CUDY GS1026PS2 24-Port Gigabit PoE+ Switch with 2 Uplink Gigabit Ports and 2 Gigabit SFP Slots 300W, 24× GbE with 802.3at/af PoE, 2× Uplink GbE + 2× Uplink SFP, 300W Power Supply, Default/Extend Modes, Watchdog under Extend Mode, Desktop, Rack-Mount, 320×207×44 mm (12.6×8.15×1.73″)

Texniki göstəricilər

24 Port
Port sayı

1000mb/s
Port sürəti

PoE+
PoE

300 W
PoE gücü

Ətraflı məlumat

GS1026PS2 1.0	
Gigabit SFP Slots	2
Gigabit RJ45 Ports	2
Gigabit RJ45 PoE Ports	24
Max Power on a Single PoE Port	30W
PoE Port Notes	PoE ports are 802.3at/af compatible.
Extend Mode Ports	#17~#24
LED	• Power • DIP Mode (SW) • PoE Status of Each PoE Port • Link/ACT of Each Ethernet Port • PoE Max Status
Power Input	AC Inlet
Physical Buttons	• Default/Extend DIP switch • PoE LED Toggle
Physical Buttons Note	The PoE Watchdog is on under the Extend mode and will attempt to reboot the plugged-in but inactive client.
Copper Speed and Distance	• Cat. 3 or higher cable: 100 meters at 10 Mbps • Cat. 5 or higher cable: 100 meters at 100 Mbps • Cat. 5e or higher cable: 100 meters at Gigabit • Cat. 5e or higher cable: 250 meters at 10 Mbps
Copper Speed and Distance Note	250-meter transmission is only available on the Extend Mode ports.
Optical Spec and Distance	Depends on the Installed Optical Module
MAC Address Table	8192
Max Switching Capacity	56 Gbps
Max Forwarding Rate	41.664 Mpps

Packet Buffer	3 Mbit
Power Methods	AC
AC	100-240V 50/60Hz
Power Supply	300W
Max Power Excluding PoE	20W
802.3 Protocols	• 802.3i 10BASE-T • 802.3u 100BASE-TX • 802.3ab 1000BASE-T • 802.3z 1000BASE-X • 802.3x Flow Control • 802.3af PoE • 802.3at PoE
Grounding Methods	Three-Prong Plug
Lightning/Surge Protection	Power: DM 2kV, CM 4kV
Environment	Operating Temperature: 0~40 ℃ (32~104 ℉) Storage Temperature: -40~70℃ (-40~158 ℉) Operating Humidity: 10~90% non-condensing Storage Humidity: 10~95% non-condensing
Dimension	320×207×44 mm 12.6×8.15×1.73 inches
Product Weight	1986 g (70.05 oz.)
Casing Material	Metal
Installation	• Desktop • Rackmount via Brackets
• GS1026PS2 • Power Cord • Mounting Kit • Installation Guide	
Retail Package Dimension	370×290×85 mm 14.57×11.42×3.35 inches
Retail Package Weight	EU: 2534 g (89.38 oz.)

Carton Net Weight	EU: 12.7 kg (28 lbs)
Carton Gross Weight	EU: 13.6 kg (29.98 lbs)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az