

HAC-HDW1200EMP-S4-0360B

2 meqapiksel HD-CVI kamera; Piksel 1920x1080; IR işıqlandırma - 50 m; f-3,6 mm; Bucaq-83°.

| | |
|-----------------------|-------------------------|
| Model | HAC-HDW1200EMP-S4-0360B |
| Brend | Dahua |
| Qoruma | IP67 |
| Növ | Analoq |
| Meqapixel | 2 MP |
| İşıqlandırma məsafəsi | 50 m |
| Obyektiv | Sabit |
| Fokus | 3.6mm |
| İşıqlandırma | İR |
| Material | Metal |
| İş mühiti | Indoor |



Specification

| | | | | | | |
|----------------------------|--|---------|-----------|----------|-----------|----------|
| Camera | | | | | | |
| Image Sensor | 2 MP CMOS | | | | | |
| Max. Resolution | 1920 (H) × 1080 (V) | | | | | |
| Scanning System | Progressive | | | | | |
| Electronic Shutter Speed | PAL: 1/25 s–1/100000 s NTSC: 1/30 s–1/100000 s | | | | | |
| Min. Illumination | 0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on) | | | | | |
| S/N Ratio | >65 dB | | | | | |
| Illumination Distance | 50 m (164.04 ft) | | | | | |
| Illuminator On/Off Control | Auto | | | | | |
| Illuminator Number | 1 (IR light) | | | | | |
| Angle Adjustment | Pan: 0°–360° Tilt: 0°–78° Rotation: 0°–360° | | | | | |
| Lens | | | | | | |
| Lens Type | Fixed-focal | | | | | |
| Lens Mount | M12 | | | | | |
| Focal Length | 2.8 mm; 3.6 mm | | | | | |
| Max. Aperture | F2.0 | | | | | |
| Field of View | 2.8 mm: H: 99°; V: 55°; D: 114° 3.6 mm: H: 83°; V: 48°; D: 105° | | | | | |
| Iris Control | Fixed | | | | | |
| Close Focus Distance | 2.8 mm: 0.6m (1.97 ft) 3.6 mm: 0.7 m (2.30 ft) | | | | | |
| DORI Distance | <table border="1"> <tr> <td>Lens</td> <td>Detect</td> <td>Observe</td> <td>Recognize</td> <td>Identify</td> </tr> </table> | Lens | Detect | Observe | Recognize | Identify |
| Lens | Detect | Observe | Recognize | Identify | | |

| | | | | |
|--------|-----------------------|----------------------|----------------------|---------------------|
| 2.8 mm | 45.1 m (147.97 ft) | 18.1 m (59.38 ft) | 9.0 m (29.53 ft) | 4.5 m (14.76 ft) |
| 3.6 mm | 50.9 m (166.99 ft) | 20.3 m (66.60 ft) | 10.2 m (33.46 ft) | 5.1 m (16.73 ft) |

| | |
|-----------------------|--|
| Video | |
| Video Frame Rate | CVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; AHD: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; TVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; CVBS: PAL: 960H; NTSC: 960H |
| Resolution | 1080p (1920 × 1080); 960H (960 × 576/960 × 480) |
| Day/Night | Auto(ICR)/Color/B/W |
| BLC | BLC; HLC; DWDR |
| WDR | DWDR |
| White Balance | Auto; Area white balance |
| Gain Control | Auto |
| Noise Reduction | 3D NR |
| Illumination Mode | Smart IR |
| Mirror | Yes |
| Privacy Masking | Off/On (8 areas, rectangle) |
| Certification | |
| Certifications | CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035; FCC: 47 CFR FCC Part 16, Subpart B |
| Port | |
| Video Output | Video output choices of CVI/TVI/AHD/CVBS by one BNC port |
| Power | |
| Power Supply | 12 VDC ± 30% |
| Power Consumption | Max 3.2 W (12 VDC, IR on) |
| Environment | |
| Operating Temperature | -40 °C to +60 °C (-40 °F to +140 °F) |
| Operating Humidity | <95% (RH), non-condensing |
| Storage Temperature | -40 °C to +60 °C (-40 °F to +140 °F) |
| Storage Humidity | <95% (RH), non-condensing |
| Protection | IP67 |
| Structure | |
| Casing Material | Metal |
| Product Dimensions | Φ106.0 mm × 93.6 mm (Φ4.17" × 3.69") |
| Net Weight | 0.44 kg (0.97 lb) |
| Gross Weight | 0.60 kg (1.32 lb) |
| Installation | Wall mount; ceiling mount; vertical pole mount |