

HAC-HDW1500MP-0280B

Dahua HAC-HDW1500MP-0280B 5 MP HD-CVI kamera; Piksel 2880x1620; IR işıqlandırma - 30 m; F2,8 mm; Bucaq-98°.



Model	HAC-HDW1500MP-0280B
Brend	Dahua
Növ	Analoq
Meqapixel	5 MP
İşıqlandırma məsafəsi	30 m
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
Qoruma	IP67
Material	Metal

Specification

Camera	
Image Sensor	1/2.7" CMOS
Effective Pixels	2592(H)×1944(V), 5MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25~1/100000s NTSC: 1/30~1/100000s
Minimum Illumination	0.02Lux/F1.85, 30IRE, 0Lux IR on
S/N Ratio	More than 65dB
IR Distance	Up to 30m (98feet)
IR On/Off Control	Auto / Manual
IR LEDs	12
Lens	
Lens Type	Fixed lens / Fixed iris
Mount Type	Board-in
Focal Length	3.6mm (2.8mm, 6mm Optional)
Max Aperture	F1.85
Angle of View	H: 77.5° (98°/49°)
Focus Control	N/A

Close Focus Distance	1400mm (900mm/2800mm) 55" (35"/110")																		
DORI Distance																			
Note: The DORI distance is a "general proximity" of distance which makes it easy to pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specification and lab test result according to EN 62676-4 which defines the criteria for Detect, Observe, Recognize and Identify respectively.																			
	<table border="1"> <thead> <tr> <th>DORI Definition</th> <th>Distance</th> </tr> </thead> <tbody> <tr> <td rowspan="3">Detect</td> <td>2.8mm: 63m(207ft)</td> </tr> <tr> <td>3.6mm: 80m(262ft)</td> </tr> <tr> <td>6mm: 120m(394ft)</td> </tr> <tr> <td rowspan="3">Observe</td> <td>2.8mm: 25m(82ft)</td> </tr> <tr> <td>3.6mm: 32m(105ft)</td> </tr> <tr> <td>6mm: 48m(157ft)</td> </tr> <tr> <td rowspan="3">Recognize</td> <td>2.8mm: 13m(43ft)</td> </tr> <tr> <td>3.6mm: 16m(53ft)</td> </tr> <tr> <td>6mm: 24m(79ft)</td> </tr> <tr> <td rowspan="3">Identify</td> <td>2.8mm: 6m(21ft)</td> </tr> <tr> <td>3.6mm: 8m(26ft)</td> </tr> <tr> <td>6mm: 12m(39ft)</td> </tr> </tbody> </table>	DORI Definition	Distance	Detect	2.8mm: 63m(207ft)	3.6mm: 80m(262ft)	6mm: 120m(394ft)	Observe	2.8mm: 25m(82ft)	3.6mm: 32m(105ft)	6mm: 48m(157ft)	Recognize	2.8mm: 13m(43ft)	3.6mm: 16m(53ft)	6mm: 24m(79ft)	Identify	2.8mm: 6m(21ft)	3.6mm: 8m(26ft)	6mm: 12m(39ft)
DORI Definition	Distance																		
Detect	2.8mm: 63m(207ft)																		
	3.6mm: 80m(262ft)																		
	6mm: 120m(394ft)																		
Observe	2.8mm: 25m(82ft)																		
	3.6mm: 32m(105ft)																		
	6mm: 48m(157ft)																		
Recognize	2.8mm: 13m(43ft)																		
	3.6mm: 16m(53ft)																		
	6mm: 24m(79ft)																		
Identify	2.8mm: 6m(21ft)																		
	3.6mm: 8m(26ft)																		
	6mm: 12m(39ft)																		
Pan / Tilt / Rotation																			
Pan/Tilt/Rotation	Pan: 0° ~ 360° Tilt: 0° ~ 90° Rotation: 0° ~ 360°																		
Video																			
Resolution	5MP (2592×1944)																		
Frame Rate	20fps@5MP, 25/30fps@4MP, 25/30fps@1080P																		
Video Output	1-channel BNC high definition video output / CVBS video output (Can switch)																		
Day/Night	Auto (ICR) / Manual																		
OSD Menu	Multi-language																		
BLC Mode	BLC / HLC / DWDR																		
WDR	DWDR																		
Gain Control	AGC																		
Noise Reduction	2D																		
White Balance	Auto / Manual																		
Smart IR	Auto / Manual																		
Certifications																			
Certifications	CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)																		
Interface																			

Audio Interface	N/A
Electrical	
Power Supply	12V DC \pm 30%
Power Consumption	Max. 3.6W (12V DC, IR on)
Environmental	
Operating Conditions	-40°C ~ +60°C (-40°F ~ +140°F) / Less than 95% RH * Start up should be done at above -40°C (-40°F)
Storage Conditions	-40°C ~ +60°C (-40°F ~ +140°F) / Less than 95% RH
Ingress Protection & Vandal Resistance	IP67
Construction	
Casing	Aluminium
Dimensions	Φ 93.4mm \times 79.4mm (Φ 3.68" \times 3.13")
Net Weight	0.28kg (0.62lb)
Gross Weight	0.38kg (0.84lb)