

HAC-HFW1200CP-A-0280B

2 meqapiksel HD-CVI kamera; Piksel 1920x1080; IR işıqlandırma - 30 m; f-2,8 mm; Bucaq-102°; Audio (mikrofon)

Model	HAC-HFW1200CP-A-0280B
Brend	Dahua
İş mühiti	Outdoor
Növ	Analoq
Meqapixel	2 MP
Mikrofon	Mic
İşıqlandırma məsafəsi	30 m
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR
Qoruma	IP67
Material	Plastik



Specification

Camera						
Image Sensor	2 MP CMOS					
Max. Resolution	1920 (H) × 1080 (V)					
Scanning System	Progressive					
Electronic Shutter Speed	PAL: 1/25 s–1/100000 s NTSC: 1/30 s–1/100000 s					
Min. Illumination	0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on)					
S/N Ratio	>65 dB					
Illumination Distance	30 m (98.43 ft)					
Illuminator On/Off Control	Auto					
Illuminator Number	2 (IR light)					
Angle Adjustment	Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360°					
Lens						
Lens Type	Fixed-focal					
Lens Mount	M12					
Focal Length	2.8 mm; 3.6 mm					
Max. Aperture	F2.0					
Field of View	2.8 mm: H: 102°; V: 60°; D: 129° 3.6 mm: H: 83°; V: 48°; D: 104°					
Iris Control	Fixed					
Close Focus Distance	2.8 mm: 0.5 m (1.64 ft) 3.6 mm: 0.7 m (2.30 ft)					
DORI Distance	<table border="1"> <tr> <td>Lens</td> <td>Detect</td> <td>Observe</td> <td>Recognize</td> <td>Identify</td> </tr> </table>	Lens	Detect	Observe	Recognize	Identify
Lens	Detect	Observe	Recognize	Identify		

2.8 mm	41.4 m (135.83 ft)	16.5 m (42.13 ft)	8.3 m (27.23 ft)	4.1 m (13.45 ft)
3.6 mm	50.9 m (166.99 ft)	20.3 m (66.60 ft)	10.2 m (33.46 ft)	5.1 m (16.73 ft)

Video	
Video Frame Rate	CVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; AHD: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; TVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; CVBS: PAL: 960H; NTSC: 960H
Resolution	1080p (1920 × 1080); 960H (960 × 576/960 × 480)
Day/Night	Auto(ICR)/Color/B/W
BLC	BLC; HLC; DWDR
WDR	DWDR
White Balance	Auto; Area white balance
Gain Control	Auto
Noise Reduction	3D NR
Illumination Mode	Smart IR
Mirror	Yes
Privacy Masking	Off/On (8 areas, rectangle)
Certification	
Certifications	CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035; FCC: 47 CFR FCC Part 15, Subpart B
Port	
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Power	
Power Supply	12 VDC ± 30%
Power Consumption	Max 2.8 W (12 VDC, IR on)
Environment	
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Humidity	<95% (RH), non-condensing
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Storage Humidity	<95% (RH), non-condensing
Protection	IP67
Structure	
Casing Material	Plastic
Product Dimensions	161.3 mm × 69.7 mm × 70.0 mm (6.35" × 2.75" × 2.75")
Net Weight	0.19 kg (0.55 lb)
Gross Weight	0.29 kg (0.64 lb)
Installation	Wall mount; ceiling mount; vertical pole mount