

HAC-HFW1200DP-0360B

2 meqapiksel HD-CVI kamera; Piksel 1920x1080; IR işıqlandırma - 80 m; f-3,6 mm; Bucaq-83°.

Model	HAC-HFW1200DP-0360B
Brend	Dahua
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	80 m
Obyektiv	Sabit
Fokus	3.6
İşıqlandırma	İR
Qoruma	IP67
Material	Metal



Specification

Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) x 1080 (V)
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s-1/100000 s NTSC: 1/30 s-1/100000 s
Min. Illumination	0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on)
S/N Ratio	>65 dB
Illumination Distance	80 m (262.47 ft)
Illuminator On/Off Control	Auto
Illuminator Number	2 (IR light)
Angle Adjustment	Pan: 0°-360° Tilt: 0°-90° Rotation: 0°-360°
Lens	
Lens Type	Fixed-focal
Lens Mount	M12
Focal Length	3.6 mm; 6 mm
Max. Aperture	F2.0

Field of View	3.6 mm: H: 83°; V: 48°; D: 104° 6 mm: H: 47°; V: 27°; D: 54°				
Iris Control	Fixed				
Close Focus Distance	3.6 mm: 0.7 m (2.30 ft) 6 mm: 2.3 m (7.55 ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	3.6 mm	50.9 m (166.99 ft)	20.3 m (66.60 ft)	10.2 m (33.46 ft)	5.1 m (16.73 ft)
	6 mm	95.1 m (312.01 ft)	38.0 m (124.67 ft)	19.0 m (62.34 ft)	9.5 m (31.17 ft)
Video					
Video Frame Rate	CVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; AHD: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; TVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; CVBS: PAL: 960H; NTSC: 960H				
Resolution	1080p (1920 × 1080); 960H (960 × 576/960 × 480)				
Day/Night	Auto(ICR)/Color/B/W				
BLC	BLC; HLC; DWDR				
WDR	DWDR				
White Balance	Auto; Area white balance				
Gain Control	Auto				
Noise Reduction	3D NR				
Illumination Mode	Smart IR				
Mirror	Yes				
Privacy Masking	Off/On (8 areas, rectangle)				
Certification					
Certifications	CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035; FCC: 47 CFR FCC Part 15, Subpart B				
Port					
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port				
Power					
Power Supply	12 VDC ± 30%				
Power Consumption	Max 4.7 W (12 VDC, IR on)				
Environment					
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)				
Operating Humidity	<95% (RH), non-condensing				
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)				
Storage Humidity	<95% (RH), non-condensing				
Protection	IP67				
Structure					
Casing Material	Plastic sunshield + metal body				
Product Dimensions	241.8 mm × 90.4 mm × 90.4 mm (9.52" × 3.56" × 3.56")				
Net Weight	0.60 kg (1.32 lb)				
Gross Weight	0.79 kg (1.74 lb)				
Installation	Wall mount; ceiling mount; vertical pole mount				