

# HAC-HFW1200TH-I4-A-0280B

2 meqapiksel HD-CVI kamera; Piksel 1920x1080; IR işıqlandırma - 40 m; f-2,8 mm; Bucaq-102°.



## Specifications

Model	HAC-HFW1200TH-I4-A-0280B
Brand	Dahua
Çalışma mühiti	Outdoor
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	40 m
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR
Mikrofon	Mic
Qoruma	IP67
Material	Metal

KEY FEATURES

Camera

Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s–1/100000 s NTSC: 1/30 s–1/100000 s
Min. Illumination	0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on)
S/N Ratio	>65 dB
Illumination Distance	40 m (131.23 ft)
Illuminator On/Off Control	Auto
Illuminator Number	1 (IR light)
Angle Adjustment	Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360°

Lens

Lens Type	Fixed-focal
Lens Mount	M12
Focal Length	2.8 mm;3.6 mm
Max. Aperture	F2.0
Field of View	2.8 mm: H: 102°; V: 60°; D: 129° 3.6 mm: H: 83°; V: 48°; D: 104°
Iris Control	Fixed
Close Focus Distance	2.8 mm: 0.5 m (1.64 ft) 3.6 mm: 0.7 m (2.30 ft)

DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	41.4 m (135.83 ft)	16.5 m (42.13 ft)	8.3 m ( 27.23 ft)	4.1 m (13.45 ft)
	3.6 mm	50.9 m (166.99 ft)	20.3 m (66.60 ft)	10.2 m (33.46 ft)	5.1 m (16.73 ft)

Video

---

<b>Video Frame Rate</b>	<b>CVI:</b> <b>PAL: 1080p@25 fps;</b> <b>NTSC: 1080p@30 fps;</b> <b>AHD:</b> <b>PAL: 1080p@25 fps;</b> <b>NTSC: 1080p@30 fps;</b> <b>TVI:</b> <b>PAL: 1080p@25 fps;</b> <b>NTSC: 1080p@30 fps;</b> <b>CVBS:</b> <b>PAL: 960H;</b> <b>NTSC: 960H</b>
<b>Resolution</b>	<b>1080p (1920 × 1080); 960H (960 × 576/960 × 480)</b>
<b>Day/Night</b>	<b>Auto(ICR)/Color/B/W</b>
<b>BLC</b>	<b>BLC; HLC; DWDR</b>
<b>WDR</b>	<b>DWDR</b>
<b>White Balance</b>	<b>Auto; Area white balance</b>
<b>Gain Control</b>	<b>Auto</b>
<b>Noise Reduction</b>	<b>3D NR</b>
<b>Illumination Mode</b>	<b>Smart IR</b>
<b>Mirror</b>	<b>Yes</b>
<b>Privacy Masking</b>	<b>Off/On (8 areas, rectangle)</b>
<b>Certification</b>	
<b>Certifications</b>	<b>CE-LVD: EN 62368-1;</b> <b>CE-EMC: EN 55032; EN 55035;</b> <b>FCC: 47 CFR FCC Part 15, Subpart B</b>
<b>Port</b>	
<b>Video Output</b>	<b>Video output choices of CVI/TVI/AHD/CVBS by one BNC port</b>
<b>Audio Input</b>	<b>One channel built-in Mic</b>
<b>Power</b>	
<b>Power Supply</b>	<b>12 VDC ± 30%</b>
<b>Power Consumption</b>	<b>Max 3.2 W (12 VDC, IR on)</b>
<b>Environment</b>	
<b>Operating Temperature</b>	<b>-40 °C to +60 °C (-40 °F to +140 °F)</b>
<b>Operating Humidity</b>	<b>&lt;95% (RH), non-condensing</b>
<b>Storage Temperature</b>	<b>-40 °C to +60 °C (-40 °F to +140 °F)</b>
<b>Storage Humidity</b>	<b>&lt;95% (RH), non-condensing</b>
<b>Protection</b>	<b>IP67</b>
<b>Structure</b>	
<b>Casing Material</b>	<b>Metal front cover + plastic rear barrel + metal bracket</b>
<b>Product Dimensions</b>	<b>240.7 mm × 90.7 mm × 90.4 mm (9.48" × 3.57" × 3.56")</b>
<b>Net Weight</b>	<b>0.41 kg (0.90 lb)</b>
<b>Gross Weight</b>	<b>0.62 kg (1.37 lb)</b>
<b>Installation</b>	<b>Wall mount; ceiling mount; vertical pole mount</b>