

# HAC-HFW1200TLP

Dahua HAC-HFW1200TLP 2MP F2.8 40m



## Specifications

Model	HAC-HFW1200TLP
Brand	Dahua
Qoruma	IP67
Növ	Analoq
Meqapixel	2 MP
??qland?rma m?saf?si	40 m
Obyektiv	Sabit
Fokus	2.8mm
??qland?rma	IR
Material	Plastik
?? mühiti	Outdoor

KEY FEATURES

Camera

Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s–1/100000 s NTSC: 1/30 s–1/100000 s
Min. Illumination	0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on)
S/N Ratio	>65 dB
Illumination Distance	40 m (131.23 ft)
Illuminator On/Off Control	Auto
Illuminator Number	2 (IR light)
Angle Adjustment	Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360°

Lens

Lens Type	Fixed-focal
Lens Mount	M12
Focal Length	2.8 mm; 3.6 mm; 6 mm
Max. Aperture	F2.0
Field of View	2.8 mm: H: 102°; V: 60°; D: 129° 3.6 mm: H: 83°; V: 48°; D: 104° 6 mm: H: 47°; V: 27°; D: 54°
Iris Control	Fixed
Close Focus Distance	2.8 mm: 0.5 m (1.64 ft) 3.6 mm: 0.7 m (2.30 ft) 6 mm: 2.3 m (7.55 ft)

DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	41.4 m (135.83 ft)	16.5 m (42.13 ft)	8.3 m ( 27.23 ft)	4.1 m (13.45 ft)
	3.6 mm	50.9 m (166.99 ft)	20.3 m (66.60 ft)	10.2 m (33.46 ft)	5.1 m (16.73 ft)
	6 mm	95.1 m (312.01 ft)	38.0 m (124.67 ft)	19.0 m (62.34 ft)	9.5 m (31.17 ft)

Video

<b>Video Frame Rate</b>	<b>CVI:</b> PAL: 1080p@25 fps; NTSC: 1080p@30 fps; <b>AHD:</b> PAL: 1080p@25 fps; NTSC: 1080p@30 fps; <b>TVI:</b> PAL: 1080p@25 fps; NTSC: 1080p@30 fps; <b>CVBS:</b> PAL: 960H; NTSC: 960H
<b>Resolution</b>	1080p (1920 × 1080); 960H (960 × 576/960 × 480)
<b>Day/Night</b>	Auto(ICR)/Color/B/W
<b>BLC</b>	BLC; HLC; DWDR
<b>WDR</b>	DWDR
<b>White Balance</b>	Auto; Area white balance
<b>Gain Control</b>	Auto
<b>Noise Reduction</b>	3D NR
<b>Illumination Mode</b>	Smart IR
<b>Mirror</b>	Yes
<b>Privacy Masking</b>	Off/On (8 areas, rectangle)
<b>Certification</b>	
<b>Certifications</b>	CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035; FCC: 47 CFR FCC Part 15, Subpart B
<b>Port</b>	
<b>Video Output</b>	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
<b>Power</b>	
<b>Power Supply</b>	12 VDC ± 30%
<b>Power Consumption</b>	Max 2.8 W (12 VDC, IR on)
<b>Environment</b>	
<b>Operating Temperature</b>	-40 °C to +60 °C (-40 °F to +140 °F)
<b>Operating Humidity</b>	<95% (RH), non-condensing
<b>Storage Temperature</b>	-40 °C to +60 °C (-40 °F to +140 °F)
<b>Storage Humidity</b>	<95% (RH), non-condensing
<b>Protection</b>	IP67
<b>Structure</b>	
<b>Casing Material</b>	Plastic
<b>Product Dimensions</b>	198.9 mm × 80.2 mm × 76.2 mm (7.83" × 3.16" × 3.00")
<b>Net Weight</b>	0.22 kg (0.49 lb)
<b>Gross Weight</b>	0.41 kg (0.90 lb)
<b>Installation</b>	Wall mount; ceiling mount; vertical pole mount