

HAC-HFW1400DP-0360B

4 MP HD-CVI kamera; Piksel 1920x1080; IR işıqlandırma - 80 m; F3,6 mm; Bucaq-87°.

Model	HAC-HFW1400DP-0360B
Brend	Dahua
Növ	Analoq
Meqapixel	4 MP
İşıqlandırma məsafəsi	80 m
Obyektiv	Sabit
Fokus	3.6
İşıqlandırma	İR
Qoruma	IP67
Material	Metal



Specification

Camera					
Image Sensor	1/2.7 inch CMOS				
Effective Pixels	2560(H)×1440(V), 4MP				
Scanning System	Progressive				
Electronic Shutter Speed	PAL: 1/25s~1/100000s NTSC: 1/30s~1/100000s				
S/N Ratio	>65dB				
Minimum Illumination	0.02Lux/F2.0, 30IRE, 0Lux IR on				
Fill Light Working Distance	80 m (262.5 ft)				
IR On/Off Control	Auto; manual				
IR LED Number	2				
Pan/Tilt/Rotation Range	Pan: 0°~360° Tilt: 0°~87° Rotation: 0°~360°				
Lens					
Lens Type	Fixed-focal				
Mount Type	M12				
Focal Length	3.6 mm; 6 mm; 8 mm				
Max. Aperture	F2.0; F2.0; F2.0				
Field of View	3.6 mm: 104° x 87° x 47° (diagonal x horizontal x vertical) 6 mm: 62° x 54° x 31° (diagonal x horizontal x vertical) 8 mm: 46° x 40° x 22° (diagonal x horizontal x vertical)				
Iris Type	Fixed iris				
Close Focus Distance	3.6 mm: 1.1 m (3.6 ft) 6 mm: 2.7 m (8.9 ft) 8 mm: 3.5 m (11.5 ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify

3.6 mm	64 m (210.0 ft)	25.6 m (84 ft)	12.8 m (42 ft)	6.4 m (21 ft)		
6 mm	106.7 m (350.1 ft)	42.7m (140.1 ft)	21.3m (69.9 ft)	10.7m (35.1 ft)		
		8 mm	142.2m (466.5 ft)	56.9m (186.7 ft)	28.4m (93.2 ft)	14.2m (46.6 ft)
Video						
Frame Rate	CVI: PAL: 4M@25fps; 1080P@25fps; NTSC: 4M@30fps; 1080P@30fps AHD: PAL: 4M@25fps; NTSC: 4M@30fps TVI: PAL: 4M@25fps; NTSC: 4M@30fps CVBS: PAL: 960H; NTSC: 960H					
Resolution	4M (2560 × 1440); 1080P (1920 × 1080); 960 H (960 × 576/960 × 480)					
Day/Night	Auto switch by ICR					
BLC	BLC/HLC/DWDR					
WDR	DWDR					
White Balance	Auto; manual					
Gain Control	Auto; manual					
Noise Reduction	2D NR					
Smart IR	Yes					
Electronic Defog	Yes					
Mirror	Off/On					
Privacy Masking	Off/On (8 area, rectangle)					
Certifications						
Certifications	CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024:2010+A1:2015, EN 55035:2017, EN50130-4:2011+A1:2014) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)					
Port						
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port					
Power						
Power Supply	12V ±30% DC					
Power Consumption	Max 4.9W (12V DC, IR on)					
Environment						
Operating Temperature	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)					
Storage Temperature	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)					
Protection Grade	IP67					
Structure						
Casing	Mental throughout the whole casing					
Camera Dimensions	241.8 mm × 90.4 mm × 90.4 mm (9.52" × 3.56" × 3.56")					
Net Weight	0.59 Kg (1.30 lb)					
Gross Weight	0.69 Kg (1.52 lb)					