eurotech
Taste of technology

**TEXNIKI SƏNƏD**

29.11.2026

DAHUA

# HAC-HFW2221DP

Kod: 00-00003312 · Kamera



DAHUA - HAC-HFW2221DP ( 3,6mm ) - 2MP HDCVI KAMERA

## Texniki göstəricilər

| | |
|---|---|
| **Analoq**<br>Növ | **2 MP**<br>Meqapixel |
| **80 m**<br>İşıqlandırma məsafəsi | **Sabit**<br>Obyektiv |
| **3.6mm**<br>Fokus | **İR**<br>İşıqlandırma |
| **Metal**<br>Material | **Outdoor**<br>İş mühiti |
| **IP67**<br>Qoruma | |

## Ətraflı məlumat

| | |
|---|---|
| Image Sensor | 1/2.7" CMOS |
| EffectivePixels | 1928(H)×1088(V), 2.1MP |
| ScanningSystem | Progressive |
| Electronic Shutter Speed | PAL: 1.3s~1/30000s<br>NTSC: 1s~1/30000s |
| MinimumIllumination | 0.03Lux/F2.0, 30IRE, 0Lux IR on |
| S/N Ratio | More than 65dB |
| IR Distance | Up to80m (262feet) |
| IR On/Off Control | Auto /Manual |
| IR LEDs | 2 |
| Lens Type | Fixed lens/ Fixed iris |
| Mount Type | Board-in |
| Focal Length | 3.6mm (6mm,8mm, 12mm Optional) |
| Max Aperture | F2.0 |
| Angle of View | H: 90° (59.4°/41.4°/26.5° ) |
| Focus Control | N/A |
| Close Focus Distance | 800mm (1800mm, 3000mm, 8400mm)<br>31.50'' ( 70.87'', 118.11'', 330.71'') |
| Pan/Tilt/Rotation | Pan: 0° ~ 360°<br>Tilt: 0° ~ 87°<br>Rotation: 0° ~ 360° |
| Certifications | CE (EN55032, EN55024, EN50130-4)<br>FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2No.60950-1) |
| Audio Interface | N/A |

| | |
|---|---|
| Power Supply | 12V DC ±25% |
| Power Consumption | Max 5.7W (12V DC,IR on) |
| Operating Conditions | -30°C ~ +60°C(-22°F ~ +140°F)/ Less than90% RH<br>* Startup should be done at above-30°C (-22°F) |
| Storage Conditions | -30°C ~ +60°C (-22°F~ +140°F) / Less than90% RH |
| Ingress Protection & Vandal Resistance | IP67 |
| Casing | Aluminium |
| Dimensions | 241.8mm×90.4mm×90.4mm (9.52"×3.56"×3.56") |
| Net Weight | 0.64kg (1.41lb) |
| Gross Weight | 0.77kg (1.69lb) |
| Resolution | 1080P (1920×1080) |

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az