eurotech
Taste of technology

**TEXNIKI SƏNƏD**

29.11.2026

DAHUA

# HAC-ME1239THP-A-PV-0280B-S2

Kod: 00-00004969 · Kamera



DAHUA HAC-ME1239THP-A-PV-0280B-S2 ( 2.8 MM ) - 2MP FULL COLOR HDCVI (OUTDOOR); Audio (səsli); Active Deterrence

## Texniki göstəricilər

| | |
|---|---|
| **Analoq**<br>Növ | **2 MP**<br>Meqapixel |
| **LED**<br>İşıqlandırma | **40 m**<br>İşıqlandırma məsafəsi |
| **Sabit**<br>Obyektiv | **2.8mm**<br>Fokus |
| **Mic**<br>Mikrofon | **IP67**<br>Qoruma |
| **Plastik**<br>Material | **Outdoor**<br>İş mühiti |

## Ətraflı məlumat

| | |
|---|---|
| **Camera** | |
| Pixel | 2 MP |
| Image Sensor | 2 MP CMOS |
| Max. Resolution | 1920 (H) × 1080 (V) |
| Scanning System | Progressive |
| Electronic Shutter Speed | PAL: 1/25 s–1/100,000 s<br>NTSC: 1/30 s–1/100,000 s |
| Min. Illumination | 0.001 lux@F1.6 (Color, 30 IRE)<br>0.0001 lux@F1.6 (B/W, 30 IRE)<br>0 lux (Illuminator on) |
| S/N Ratio | >65 dB |
| Illumination Distance | IR: 40 m (131.23 ft)<br>Warm light: 40 m (131.23 ft) |
| Illuminator On/Off Control | Auto/Manual |
| Illuminator Number | 2 (IR light)<br>2 (Warm light) |
| Pan/Tilt/Rotation Range | Pan: 0°–360°<br>Tilt: 0°–78°<br>Rotation: 0°–360° |
| **Lens** | |
| Lens Type | Fixed-focal |
| Lens Mount | M12 |
| Focal Length | 2.8 mm<br>3.6 mm |
| Max. Aperture | F1.6 |

| | | | | | |
|---|---|---|---|---|---|
| Field of View | 2.8 mm: H: 108°; V: 58°; D: 127°<br>3.6 mm: H: 86°; V: 46°; D: 101° | | | | |
| Iris Control | Fixed | | | | |
| Close Focus Distance | 2.8 mm: 0.7 m (2.29 ft)<br>3.6 mm: 1.1 m (3.61 ft) | | | | |
| DORI Distance | Lens | Detect | Observe | Recognize | Identify |
| | 2.8 mm | 42.2 m (138.45 ft) | 16.9 m (55.45 ft) | 8.4 m (27.56 ft) | 4.2 m (13.78 ft) |
| | 3.6 mm | 53.7 m (176.18 ft) | 21.5 m (70.54 ft) | 10.7 m (35.10 ft) | 5.4 m (17.72 ft) |
| **Video** | | | | | |
| Video Frame Rate | CVI:<br>PAL: 1080p@25 fps;<br>NTSC: 1080p@30 fps;<br>AHD:<br>PAL: 1080p@25 fps;<br>NTSC: 1080p@30 fps;<br>TVI:<br>PAL: 1080p@25 fps;<br>NTSC: 1080p@30 fps;<br>CVBS:<br>PAL: 960 × 576H;<br>NTSC: 960 × 480H | | | | |
| Resolution | 1080p (1920 × 1080); 960H (960 × 576/960 × 480) | | | | |
| Day/Night | Auto (ICR)/Color/B/W | | | | |
| BLC | BLC; HLC; WDR | | | | |
| WDR | 130 dB | | | | |
| White Balance | Auto; Area white balance | | | | |
| Gain Control | Auto/Manual | | | | |
| Noise Reduction | 3D NR | | | | |

| | |
|---|---|
| Smart Illumination | Yes |
| Mirror | Off/On |
| Privacy Masking | Off/On (8 areas, rectangle) |
| Illuminator | Smart IR&WL; WL Mode; IR Mode |
| **Active Deterrence** | |
| Sound Warning | Audio1: alarm<br>Audio2: No parking here<br>Audio3: Private land no entry.<br>Audio4: Warning zone keep off<br>Audio5: Welcome<br>Volume: high/medium/low;<br>duration: 5 s–60 s; 110 dB |
| Red/Blue Light Warning | Flash: 5 s–60 s; frequency: high/medium/low |
| **Certification** | |
| Certifications | CE (EN55032:2015, EN61000-3-2:2014, EN61000-3-3:2013, EN55024:2010+A1:2015, EN55035:2017, EN50130-4:2011+A1:2014, EN62368-1:2014+A11:2017)<br>FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014)<br>UL (UL62368-1+CAN/CSA C22.2 No.62368-1-14) |
| **Port** | |
| Video Output | Video output choices of CVI/TVI/AHD/CVBS by one BNC port |
| Audio Input | One channel built-in MIC (-A) |
| **Power** | |
| Power Supply | 12 VDC ± 30% (It is recommended to use a power adapter to supply the power for one camera) |
| Power Consumption | Max 7.6 W (12 VDC, IR on) |
| **Environment** | |
| Operating Temperature | –40 °C to +60 °C (–40 °F to +140 °F) |

| | |
|---|---|
| Operating Humidity | <95% (RH), non-condensing |
| Storage Temperature | –40 °C to +60 °C (–40 °F to +140 °F) |
| Protection | IP67 |
| **Structure** | |
| Casing Material | Metal front cover + plastic rear barrel + metal bracket |
| Product Dimensions | 240.7 mm × Φ90.7 mm (9.48" × Φ3.57") |
| Packaging Dimensions | 299 mm × 119 mm × 111 mm (11.77" × 4.69" × 4.37") |
| Net Weight | 0.44 kg (0.97 lb) |
| Gross Weight | 0.70 kg (1.54 lb) |
| Installation | Wall mount; ceiling mount; vertical pole mount |

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az