

HAC-ME1500EP-0280B

5 MP HD-CVI kamera; Piksel 1920x1080; IR işıqlandırma - 20 m; F2.8 mm; Bucaq-99°.



Model	HAC-ME1500EP-0280B
Brend	Dahua
Qoruma	IP67
Növ	Analoq
Meqapixel	5 MP
İşıqlandırma məsafəsi	20 m
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR
Material	Plastik
İş mühiti	Indoor

Specification

Camera		
Image Sensor	1/2.7" CMOS	
Effective Pixels	2592(H)×1944(V), 5MP	
Scanning System	Progressive	
Electronic Shutter Speed	PAL: 1/25~1/100000s NTSC: 1/30~1/100000s	
Minimum Illumination	0.02Lux/F2.0(Color), 30IRE, 0Lux IR on	
S/N Ratio	More than 65dB	
IR Distance	Up to 20m (66feet)	
IR On/Off Control	Auto / Manual	
IR LEDs	1	
Lens		
Lens Type	Fixed lens / Fixed iris	
Mount Type	Board-in	
Focal Length	3.6mm (2.8mm optional)	
Max Aperture	F2.0	
Angle of View	H: 77.5°(99°)	
Focus Control	N/A	
Close Focus Distance	1400mm (800mm) 55" (31")	
DORI Distance		
Note: The DORI distance is a "general proximity" of distance which makes it easy to pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specification and lab test result according to EN 62676-4 which defines the criteria for Detect, Observe, Recognize and Identify respectively.		
	DORI Definition	Distance

Detect	25px/m (8px/ft)	2.8mm: 56m(184ft) 3.6mm: 80m(262ft)
Observe	63px/m (19px/ft)	2.8mm: 22m(73ft) 3.6mm: 32m(105ft)
Recognize	125px/m (38px/ft)	2.8mm: 11m(37ft) 3.6mm: 16m(52ft)
Identify	250ppm (76px/ft)	2.8mm: 6m(18ft) 3.6mm: 8m(26ft)
Pan / Tilt / Rotation		
Pan/Tilt/Rotation	Pan: 0° ~ 360° Tilt: 0° ~ 90° Rotation: 0° ~ 360°	
Video		
Resolution	5MP (2592x1944)	
Frame Rate	20fps@5MP, 25/30fps@4MP, 25/30fps@1080P	
Video Output	1-channel BNC high definition video output / CVBS video output (Can switch)	
Day/Night	Auto (ICR) / Manual	

OSD Menu	Multi-language
BLC Mode	BLC / HLC / DWDR
WDR	DWDR
Gain Control	AGC
Noise Reduction	2D
White Balance	Auto / Manual
Smart IR	Auto / Manual
PIR	
Detection	Passive infrared
Detection Range	10m, 110°
Installation height	Default bracket, wall mount, 2.2-3m
Certifications	
Certifications	CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
Interface	
Audio Interface	N/A
Eelectrical	
Power Supply	12V DC ±30%
Power Consumption	Max 4.5W (12V DC, IR on)
Environmental	
Operating Conditions	-10°C ~ +50°C (+14°F ~ +122°F) / Less than 95% RH * Start up should be done at above -10°C (14°F)
Storage Conditions	-10°C ~ +50°C (+14°F ~ +122°F) / Less than 95% RH
Ingress Protection & Vandal Resistance	IP67
Construction	
Casing	Aluminium (Inner Core) + Plastic (Cover)

Dimensions	Φ110mm×96.1mm(Φ4.33"×3.78")
Net Weight	0.28kg (0.61lb)
Gross Weight	0.42kg (0.93lb)