

# HAC-T1A11P-0280B

NVR for IP Cameras



## Specifications

Model	HAC-T1A11P-0280B
Brand	Dahua
Material	Plastik
?? mühiti	Indoor
Növ	Analoq
Meqapixel	1 MP
???qland?rma m?saf?si	20 m
Fokus	2.8mm
Obyektiv	Sabit
???qland?rma	İR

KEY FEATURES

Camera

Pixel	1 MP
Image Sensor	1/2.7" CMOS
Max. Resolution	1280(H)×720(V), 1MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s–1/100,000 s NTSC: 1/30 s–1/100,000 s
Min. Illumination	0.04Lux/F2.4, 30IRE, 0Lux IR on

S/N Ratio	>65 dB
Illumination Distance	20 m (65.62 ft)
Illuminator On/Off Control	Auto/Manual
Illuminator Number	IR light

Pan/Tilt/Rotation Range	Pan: 0°–360°
	Tilt: 0°–78°
	Rotation: 0°–360°

Lens

Lens Type	Fixed-focal
Lens Mount	Board-in
Focal Length	2.8mm(3.6mm optional)
Max. Aperture	F2.4
Field of View	H: 93°(57.6°) V: 48°(32°)

Iris Control	Fixed
--------------	-------

Close Focus Distance	800mm 31.50"
----------------------	--------------

DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	51m(167ft)	20m(66ft)	10m(33ft)	5m(17ft)
	3.6 mm	51m(167ft)	20m(66ft)	10m(33ft)	5m(17ft)

Video

Video Frame Rate	25/30fps@720P
Resolution	720P (1280×720)
Day/Night	Auto (ICR)/Color/B/W
BLC	BLC; HLC; DWDR
WDR	DWDR
White Balance	Auto / Manual

---

<b>Gain Control</b>	<b>Auto/Manual</b>
<b>Noise Reduction</b>	<b>2D NR</b>
<b>Smart Illumination</b>	<b>Auto / Manual</b>
<b>Mirror</b>	<b>Yes</b>
<b>Privacy Masking</b>	<b>Off/On (8 areas, rectangle)</b>
<b>Certification</b>	
<b>Certifications</b>	<b>CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014)</b>
<b>Port</b>	
<b>Video Output</b>	<b>1-channel BNC high definition video output / CVBS video output (Can switch)</b>
<b>Power</b>	
<b>Power Supply</b>	<b>12 VDC ± 30%</b>
<b>Power Consumption</b>	<b>Max. 2.3 W (12 VDC, IR on)</b>
<b>Environment</b>	
<b>Operating Temperature</b>	<b>-40 °C to +60 °C (-40 °F to 140 °F)</b>
<b>Operating Humidity</b>	<b>&lt;95% (RH), non-condensing</b>
<b>Storage Temperature</b>	<b>-40 °C to +60 °C (-40 °F to +140 °F)</b>
<b>Protection</b>	<b>NA</b>
<b>Structure</b>	
<b>Casing</b>	<b>Plastic</b>
<b>Product Dimensions</b>	<b>85mm×85mm×69mm(3.35"×3.35"×2.72")</b>
<b>Packaging Dimensions</b>	<b>164 mm × 79 mm × 90 mm (6.46" × 3.11" × 3.54")</b>
<b>Net Weight</b>	<b>0.09kg (0.20lb)</b>
<b>Gross Weight</b>	<b>0.13kg (0.27lb)</b>
<b>Installation</b>	<b>Wall mount; ceiling mount; horizontal pole mount</b>