

# HAC-T1A11P-0280B



Model	HAC-T1A11P-0280B
Brend	Dahua
Növ	Analoq
Meqapixel	1 MP
İşıqlandırma məsafəsi	20 m
Fokus	2.8
Obyektiv	Sabit
İşıqlandırma	İR
Material	Plastik

## Specification

Camera	
Pixel	1 MP
Image Sensor	1/2.7" CMOS
Max. Resolution	1280(H)×720(V), 1MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s–1/100,000 s NTSC: 1/30 s–1/100,000 s
Min. Illumination	0.04Lux/F2.4, 30IRE, 0Lux IR on
S/N Ratio	>65 dB
Illumination Distance	20 m (65.62 ft)
Illuminator On/Off Control	Auto/Manual
Illuminator Number	IR light
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–78° Rotation: 0°–360°
Lens	
Lens Type	Fixed-focal
Lens Mount	Board-in
Focal Length	2.8mm(3.6mm optional)
Max. Aperture	F2.4
Field of View	H: 93°(57.6°) V: 48°(32°)
Iris Control	Fixed

Close Focus Distance	800mm 31.50"				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	51m(167ft)	20m(66ft)	10m(33ft)	5m(17ft)
	3.6 mm	51m(167ft)	20m(66ft)	10m(33ft)	5m(17ft)
Video					
Video Frame Rate	25/30fps@720P				
Resolution	720P (1280×720)				
Day/Night	Auto (ICR)/Color/B/W				
BLC	BLC; HLC; DWDR				
WDR	DWDR				
White Balance	Auto / Manual				
Gain Control	Auto/Manual				
Noise Reduction	2D NR				
Smart Illumination	Auto / Manual				
Mirror	Yes				
Privacy Masking	Off/On (8 areas, rectangle)				
Certification					
Certifications	CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014)				
Port					
Video Output	1-channel BNC high definition video output / CVBS video output (Can switch)				
Power					
Power Supply	12 VDC ± 30%				
Power Consumption	Max. 2.3 W (12 VDC, IR on)				
Environment					
Operating Temperature	-40 °C to +60 °C (-40 °F to 140 °F)				
Operating Humidity	<95% (RH), non-condensing				
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)				
Protection	NA				
Structure					
Casing	Plastic				
Product Dimensions	85mm×85mm×69mm(3.35"×3.35"×2.72")				
Packaging Dimensions	164 mm × 79 mm × 90 mm (6.46" × 3.11" × 3.54")				
Net Weight	0.09kg (0.20lb)				
Gross Weight	0.13kg (0.27lb)				
Installation	Wall mount; ceiling mount; horizontal pole mount				