MERCUSYS

Halo H32G(2-pack)

Kod: 00-00005295 · Access Pointlər



MERCUSYS Halo H32G(2-pack) AC1200 Mesh Wi-Fi sistemi ilə evinizin hər küncündə sürətli və stabil internet əldə edin – geniş əhatə dairəsi və asan quraşdırma ilə mükəmməl şəbəkə təcrübəsi.

Texniki göstəricilər

WiFi5
WIFI

Mesh
Mesh

50+
Qoşulma sayı

Dual band
Genişlik

2.4Ghz/5Ghz
Tezlik

Ətraflı məlumat

Category	Details
Wireless Standards	IEEE 802.11 a/n/ac 5 GHz IEEE 802.11 b/g/n 2.4 GHz
WiFi Speeds	867 Mbps on 5 GHz, 300 Mbps on 2.4 GHz
Reception Sensitivity	**2.4GHz:** 11g 6Mbps: -96dBm 11g 54Mbps: -78dBm 11n HT20 MCS7: -76dBm 11n HT40 MCS7: -73dBm **5GHz:** 11a 6Mbps: -95dBm 11a 54Mbps: -77dBm 11ac VHT20 MCS8: -72dBm 11ac VHT40 MCS9: -67dBm 11ac VHT80 MCS9: -63dBm
Transmission Power	2.4 GHz < 20dBm (EIRP) 5 GHz < 23dBm (EIRP)
Wireless Security	WPA-PSK/WPA2-PSK
Mesh Protocol	802.11k/v/r
Hardware Dimensions	3.5 × 3.5 × 3.5 in (88 × 88 × 88 mm)
Interfaces	**Halo H30G:** 2× Gigabit Ports (WAN/LAN auto-sensing) **Halo H30:** 2× 10/100 Mbps Ports
Button	Reset button
Software Operation Modes	Router, Access Point
Quality of Service	WMM
WAN Type	Dynamic IP/Static IP/PPPoE/L2TP/PPTP
Management	Local Management, Remote Management, Multi-Managers
DHCP	Server, Client
Firewall Security	SPI Firewall
Protocols	Supports IPv4 and IPv6

Category	Details
Guest Network	2.4 GHz Guest Network x 1 5 GHz Guest Network x 1
Package Contents	1× Halo H30G Unit + 1× Halo H30 Unit 1× RJ45 Ethernet Cable 2× Power Adapters 1× Quick Installation Guide
Environment	Operating Temperature: 0°C40°C (32°F104°F) Operating Humidity: 10%~90% Non-Condensing Storage Humidity: 5%~90% Non-Condensing

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az