

HAP AC3 (RBD53IG-5HACD2HND)

MikroTik hAP ac³ (RBD53iG-5HacD2HnD) – 5 gigabit port, güclü dual-band Wi-Fi (2.4 GHz və 5 GHz) və yüksək əhatə qabiliyyəti ilə ev və ofis şəbəkələri üçün ideal routerdir. Güclü prosessoru və geniş funksiyaları ilə stabil və sürətli internet bağlantısı təmin edir.



Specifications

Model	HAP AC3 (RBD53iG-5HacD2HnD)
Brand	Mikrotik
WIFI	WiFi5
Geni?lik	Dual band
Port sür?ti	1000 mb/s
Tezlik	2.4Ghz/5Ghz
Qo?ulma say?	200+

KEY FEATURES

Details	
Product code	RBD53iG-5HacD2HnD
Architecture	ARM 32bit
CPU	IPQ-4019
CPU core count	4
CPU nominal frequency	448-896 (auto) MHz
Switch chip model	IPQ-4019
Dimensions	251 x 129 x 39 mm
RouterOS license	4
Operating System	RouterOS
Size of RAM	256 MB
Storage size	128 MB
Storage type	NAND
MTBF	Approximately 200'000 hours at 25C
Tested ambient temperature	-40°C to 70°C
IPsec hardware acceleration	Yes
Details	
Wireless 2.4 GHz Max data rate	300 Mbit/s
Wireless 2.4 GHz number of chains	2
Wireless 2.4 GHz standards	802.11b/g/n
Antenna gain dBi for 2.4 GHz	3
Wireless 2.4 GHz chip model	IPQ-4019
Wireless 2.4 GHz generation	Wi-Fi 4
Wireless 5 GHz Max data rate	867 Mbit/s
Wireless 5 GHz number of chains	2
Wireless 5 GHz standards	802.11a/n/ac
Antenna gain dBi for 5 GHz	5.5
Wireless 5 GHz chip model	IPQ-4019
Wireless 5 GHz generation	Wi-Fi 5
WiFi speed	AC1200
Details	
10/100/1000 Ethernet ports	5
Number of 1G Ethernet ports with PoE-out	1
Details	
Number of USB ports	1
USB Power Reset	Yes
USB slot type	USB type A
Max USB current (A)	1
Details	
Number of DC inputs	2 (DC jack, PoE-IN)
DC jack input Voltage	12-28 V
Max power consumption	30 W

Details	
Max power consumption without attachments	12 W
Cooling type	Passive
PoE in	Passive PoE
PoE in input Voltage	18-28 V
Details	
PoE-out ports	Ether5
PoE out	Passive PoE
Details	
Certification	CE, FCC, IC, EAC, ROHS
IP	IP20
Details	
Mode button	Yes