MIKROTIK

HAP AC3 (RBD53iG-5HacD2HnD)

Kod: 00-00001665 · Routerlər



MikroTik hAP ac³ (RBD53iG-5HacD2HnD) – 5 gigabit port, güclü dual-band Wi-Fi (2.4 GHz və 5 GHz) və yüksək əhatə qabiliyyəti ilə ev və ofis şəbəkələri üçün ideal routerdir. Güclü prosessoru və geniş funksiyaları ilə stabil və sürətli internet bağlantısı təmin edir.

Texniki göstəricilər

WiFi5	WIFI
Dual band	Genişlik
1000 mb/s	Port sürəti
2.4Ghz/5Ghz	Tezlik
200+	Qoşulma sayı

Ətraflı məlumat

Details	
Product code	RBD53iG-5HacD2HnD
Architecture	ARM 32bit
CPU	IPQ-4019
CPU core count	4
CPU nominal frequency	448-896 (auto) MHz
Switch chip model	IPQ-4019
Dimensions	251 x 129 x 39 mm
RouterOS license	4
Operating System	RouterOS
Size of RAM	256 MB
Storage size	128 MB
Storage type	NAND
MTBF	Approximately 200'000 hours at 25C
Tested ambient temperature	-40°C to 70°C
IPsec hardware acceleration	Yes
Details	
Wireless 2.4 GHz Max data rate	300 Mbit/s
Wireless 2.4 GHz number of chains	2
Wireless 2.4 GHz standards	802.11b/g/n
Antenna gain dBi for 2.4 GHz	3
Wireless 2.4 GHz chip model	IPQ-4019
Wireless 2.4 GHz generation	Wi-Fi 4
Wireless 5 GHz Max data rate	867 Mbit/s
Wireless 5 GHz number of chains	2
Wireless 5 GHz standards	802.11a/n/ac

Details	
Antenna gain dBi for 5 GHz	5.5
Wireless 5 GHz chip model	IPQ-4019
Wireless 5 GHz generation	Wi-Fi 5
WiFi speed	AC1200
Details	
10/100/1000 Ethernet ports	5
Number of 1G Ethernet ports with PoE-out	1
Details	
Number of USB ports	1
USB Power Reset	Yes
USB slot type	USB type A
Max USB current (A)	1
Details	
Number of DC inputs	2 (DC jack, PoE-IN)
DC jack input Voltage	12-28 V
Max power consumption	30 W
Max power consumption without attachments	12 W
Cooling type	Passive
PoE in	Passive PoE
PoE in input Voltage	18-28 V
Details	
PoE-out ports	Ether5
PoE out	Passive PoE
Details	
Certification	CE, FCC, IC, EAC, ROHS
IP	IP20
Details	

Details	
Mode button	Yes

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az