HIKVISION

iDS-7108HQHI-M1/S

Kod: 00-00004036 · Videoregistrator



iDS-7108HQHI-M1/S 8-ch 1080P Mini 1U H.265 AcuSense DVR Hikvision

Texniki göstəricilər

XVR	**8 kanal**
Növ	Kanal sayı
5 MP	**1 HDD**
Meqapixel	Max HDD sayı
10 TB	
Max HDD həcmi	

Ətraflı məlumat

Motion Detection 2.0	
Human/Vehicle Analysis	Deep learning-based motiondetection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leavesand lights; Quick searchby object or event typeis supported;
Perimeter Protection	
Human/Vehicle Analysis	Up to 4-ch
Facial Detection	
Facial Detection and Capture	Face picturedetection, face picturesearch
Recording	
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding Resolution	When 1080p Litemode is not enabled: 3K lite/5 MP lite/4 MP lite/1080p/720p/ VGA/WD1/4CIF/CIF; When1080p Lite modeis enabled: 3K lite/5 MP lite/4MP lite/1080p lite/ 720p lite/VGA/WD1/4CIF/CIF
Video Bitrate	32 Kbps to 6 Mbps
Dual-stream	Support
Stream Type	Video, Video& Audio
Audio Compression	G.711u
Audio Bitrate	64 Kbps
Video and Audio	

IP Video Input	2-ch (upto 10-ch) Enhanced IP mode on: 4-ch (up to 12-ch), each up to 4 MbpsUp to 6 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
Analog VideoInput	8-ch BNC interface (1.0 Vp-p,75 Ω), supporting coaxitron connection
HDTVI Input	3K(2960 x 1665)@20 fps, 5 MP(2560× 1944)@20 fps, 4 MP(2560× 1440)@30 fps, 4 MP(2560 × 1440)@25 fps,1080p@30 fps, 1080p@25 fps, 720p@30 fps, 720p@25 fps
AHD Input	5 MP(2592 × 1944)@20fps,4 MP(2560 × 1440)@30 fps, 4 MP(2560× 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30 fps, 720p@25 fps
HDCVI Input	5 MP(2592 × 1944)@20 fps,4 MP(2560 × 1440)@30 fps, 4 MP(2560× 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30fps, 720p@25 fps
CVBS Input	Support
HDMI Output	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280 ×720/60Hz
VGA Output	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280 ×720/60Hz
Video OutputMode	HDMI/VGA simultaneous output
Audio Input	1-ch, RCA (2.0 Vp-p, 1 KΩ) 8-ch via coaxial cable
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (usingthe first audioinput)
Synchronous Playback	8-ch

Network	
Total Bandwidth	96 Mbps
Remote Connection	64
Network Protocol	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
Network Interface	1, RJ45 10/100Mbps self-adaptive Ethernet interface
Wi-Fi	Connectable to Wi-Fi network by Wi-Fi dongle through USB interface
Auxiliary Interface	
SATA	1 SATA interface
Capacity	Up to 10 TBcapacity for each disk
Alarm In/Out	N/A
USB Interface	Real panel: 2 × USB 2.0
General	
Power Supply	12 VDC, 1.33 A
Consumption	≤ 12 W (without HDD)
Working Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	200 × 200 × 45 mm (7.9 × 7.9 × 1.8 inch)
Weight	≤ 1 kg (without HDD,2.2 lb.)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az