

# IDS-7108HQHI-M1/S

iDS-7108HQHI-M1/S 8-ch 1080P Mini 1U H.265 AcuSense DVR Hikvision



## Specifications

Model	iDS-7108HQHI-M1/S
Brand	Hikvision
Növ	XVR
Kanal say?	8 kanal
Meqapixel	5 MP
Max HDD say?	1 HDD
Max HDD h?cmi	10 TB

## KEY FEATURES

<b>Motion Detection 2.0</b>	<p><b>Deep learning-based motiondetection 2.0</b></p> <p>is enabled by default for all analog channels,</p>
<b>Human/Vehicle Analysis</b>	<p>it can classify human and vehicle, and</p> <p>extremely reduce false alarms caused by</p> <p>objects like leavesand lights;</p> <p>Quick searchby object or event typeis supported;</p>
<b>Perimeter Protection</b>	
<b>Human/Vehicle Analysis</b>	Up to 4-ch
<b>Facial Detection</b>	
<b>Facial Detection and Capture</b>	Face picturedetection, face picturesearch
<b>Recording</b>	
<b>Video Compression</b>	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
	When 1080p Litemode is not enabled:
	3K lite/5 MP lite/4 MP lite/1080p/720p/
<b>Encoding Resolution</b>	VGA/WD1/4CIF/CIF;
	When1080p Lite modeis enabled:
	3K lite/5 MP lite/4MP lite/1080p lite/
	720p lite/VGA/WD1/4CIF/CIF
<b>Video Bitrate</b>	32 Kbps to 6 Mbps
<b>Dual-stream</b>	Support
<b>Stream Type</b>	Video, Video& Audio
<b>Audio Compression</b>	G.711u
<b>Audio Bitrate</b>	64 Kbps
<b>Video and Audio</b>	2-ch (upto 10-ch)
	Enhanced IP mode on:
<b>IP Video Input</b>	4-ch (up to 12-ch), each up to 4 MbpsUp to 6 MP resolution
	Support H.265+/H.265/H.264+/H.264 IP cameras
	8-ch
<b>Analog VideoInput</b>	BNC interface (1.0 Vp-p,75 Ω), supporting coaxitron connection

<b>HDTVI Input</b>	3K(2960 x 1665)@20 fps, 5 MP(2560× 1944)@20 fps, 4 MP(2560× 1440)@30 fps, 4 MP(2560 × 1440)@25 fps,1080p@30 fps, 1080p@25 fps, 720p@30 fps, 720p@25 fps
<b>AHD Input</b>	5 MP(2592 × 1944)@20fps,4 MP(2560 × 1440)@30 fps, 4 MP(2560× 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30 fps, 720p@25 fps
<b>HDCVI Input</b>	5 MP(2592 × 1944)@20 fps,4 MP(2560 × 1440)@30 fps, 4 MP(2560× 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30fps, 720p@25 fps
<b>CVBS Input</b>	Support
<b>HDMI Output</b>	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280 ×720/60Hz
<b>VGA Output</b>	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280 ×720/60Hz
<b>Video OutputMode</b>	HDMI/VGA simultaneous output
<b>Audio Input</b>	1-ch, RCA (2.0 Vp-p, 1 KΩ)
<b>Audio Output</b>	8-ch via coaxial cable
<b>Two-Way Audio</b>	1-ch, RCA (Linear, 1 KΩ)
<b>Synchronous Playback</b>	1-ch, RCA (2.0 Vp-p, 1 KΩ) (usingthe first audioinput)
<b>Network</b>	8-ch
<b>Total Bandwidth</b>	96 Mbps
<b>Remote Connection</b>	64
<b>Network Protocol</b>	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
<b>Network Interface</b>	1, RJ45 10/100Mbps self-adaptive Ethernet interface
<b>Wi-Fi</b>	Connectable to Wi-Fi network by Wi-Fi dongle through USB interface
<b>Auxiliary Interface</b>	
<b>SATA</b>	1 SATA interface
<b>Capacity</b>	Up to 10 TBcapacity for each disk
<b>Alarm In/Out</b>	N/A
<b>USB Interface</b>	Real panel: 2 × USB 2.0
<b>General</b>	
<b>Power Supply</b>	12 VDC, 1.33 A
<b>Consumption</b>	≤ 12 W (without HDD)
<b>Working Temperature</b>	-10 °C to +55 °C (+14 °F to +131 °F)
<b>Working Humidity</b>	10% to 90%
<b>Dimension (W × D × H)</b>	200 × 200 × 45 mm (7.9 × 7.9 × 1.8 inch)
<b>Weight</b>	≤ 1 kg (without HDD,2.2 lb.)