IDS-7116HQHI-M1/S

NVR for IP Cameras

Specifications

Model	iDS-7116HQHI-M1/S
Brand	Hikvision
Növ	XVR
Kanal say?	16 kanal
Meqapixel	4 MP
Max HDD say?	1 HDD
Max HDD h?cmi	10 TB

© 2026 Hikvision. All rights reserved. | Eurotechnology

© 2026 Hikvision. All rights reserved. | Eurotechnology

KEY FEATURES

Motion Detection 2.0	
	Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;
Human/Vehicle Analysis	Quick searchby object or event typeis supported;
Perimeter Protection	
Line Crossing	
Detection/Intrusion Detection4-ch	
Facial Detection	
Facial Detection and Capture	Face picturedetection, face picture search

Recording

Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding Resolution	When 1080pLite mode is not enabled: 3K lite/5 MP lite/4 MP lite /1080p/720p/VGA/WD1/ 4CIF/CIF; When 1080p Lite mode is enabled: 3K lite/5MP lite/4 MP lite/1080p lite/720p lite/VGA/WD1/4CIF/CIF
Frame Rate	Main stream: When 1080pLite mode notenabled: For 3K stream access: 3K lite@12fps;4 MP lite/1080p@15fps; 720p/WD1/4CIF/VGA/CIF@20fps For 5 MP stream access: 5 MP lite@12fps;4 MP lite/1080p@15fps;720p/WD1/4CIF/VGA/CIF@20fps For 4 MP stream access: 4 MP lite/1080p@15fps; 720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) For 1080p streamaccess: 1080p/720p@15fps; VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) For 720p streamaccess: 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) When 1080p Lite mode enabled: 3K lite/5 MP lite@12fps;4 MP lite@15fps;1080p lite/720p lite/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) Sub-stream: WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)
Video Bitrate	32 Kbps to 6 Mbps
Dual-stream	Support
Stream Type	Video, Video& Audio

Audio Compression	G.711u
Audio Bitrate	64 Kbps
Video and Audio	