

# IDS-7208HQHI-M1/S

## IDS-7208HQHI-M1/S AcuSense DIGITAL VIDEO RECORDER HIKVISION



Model	IDS-7208HQHI-M1/S
Brend	Hikvision
Növ	XVR
Kanal sayı	8 kanal
Meqapixel	4 MP
Max HDD sayı	1 HDD
Max HDD həcmi	10 TB

## Specification

Motion Detection 2.0	
	Deep learning-based motiondetection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;
Human/Vehicle Analysis	Quick searchby object or event typeis supported;
Perimeter Protection	
Human/Vehicle Analysis	Up to 4-ch
Facial Detection	
Facial Detection and Capture	Face picture detection, face picture search
Recording	
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Video Bitrate	32 Kbps to 6Mbps
Dual-stream	Support
Stream Type	Video, Video& Audio
Audio Compression	G.711u
Audio Bitrate	64 Kbps
Video and Audio	

<b>IP Video Input</b>	2-ch (up to 10-ch) Up to 6 MP resolution Enhanced IP mode on: 4-ch (up to 12-ch), each up to 4 Mbps Support H.265+/H.265/H.264+/H.264 IP cameras
<b>Analog Video Input</b>	8-ch; BNC interface (1.0Vp-p, 75 Ω), supporting coaxitron connection
<b>HDMI Output</b>	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, HDMI/VGA simultaneous output
<b>CVBS Input</b>	PAL/NTSC
<b>CVBS Output</b>	1-ch, BNC (1.0Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
<b>Synchronous playback</b>	8-ch
<b>HDTVI Input</b>	3K(2960 × 1665)@20 fps, 5 MP(2560 × 1944)@20 fps, 4 MP(2560 × 1440)@30 fps, 4MP(2560 × 1440)@25 fps, 1080p@30 fps, 1080p@25 fps, 720p@30 fps, 720p@25 fps
<b>VGA Output</b>	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
<b>AHD Input</b>	5 MP(2560 × 1944)@20 fps, 4 MP(2560 × 1440)@30 fps, 4 MP(2560 × 1440)@25 fps, 1080p@30 fps, 1080p@25 fps, 720p@30fps, 720p@25 fps
<b>HDCVI Input</b>	5 MP(2592 × 1944)@20 fps, 4 MP(2560 × 1440)@30 fps, 4 MP(2560 × 1440)@25 fps, 1080p@30 fps, 1080p@25 fps, 720p@30fps, 720p@25 fps
<b>Audio Output</b>	1-ch, RCA (Linear, 1 KΩ)
<b>Audio Input</b>	1-ch, RCA (2.0 Vp-p, 1 KΩ); 8-ch via coaxial cable
<b>Two-Way Audio</b>	1-ch, RCA (2.0Vp-p, 1 KΩ) (using the first audio input)
<b>Network</b>	
<b>Total Bandwidth</b>	96 Mbps
<b>Network Protocol</b>	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
<b>Remote Connection</b>	64
<b>Network Interface</b>	1, RJ45 10M/100M self-adaptive Ethernet interface
<b>Auxiliary Interface</b>	
<b>SATA</b>	1 SATA interface
<b>Capacity</b>	Up to 10 TB capacity for each disk
<b>Serial Interface</b>	RS-485 (half-duplex)
<b>USB Interface</b>	2 × USB 2.0
<b>Alarm In/Out</b>	N/A
<b>General</b>	
<b>Power Supply</b>	12 VDC
<b>Consumption</b>	≤ 18 W
<b>Working Temperature</b>	-10 °C to +55 °C (+14 °F to +131 °F)

---

Working Humidity	10% to 90%
Dimension (W × D × H)	315 × 242 × 45 mm (12.4× 9.5 × 1.8 inch)
Weight	≤ 1.78 kg (3.9lb)