

# IDS-7208HQHI-M1/S

IDS-7208HQHI-M1/S AcuSense DIGITAL VIDEO RECORDER HIKVISION



## Specifications

Model	IDS-7208HQHI-M1/S
Brand	Hikvision
Növ	XVR
Kanal say?	8 kanal
Meqapixel	4 MP
Max HDD say?	1 HDD
Max HDD h?cmi	10 TB

## KEY FEATURES

### Motion Detection 2.0

Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;

### Human/Vehicle Analysis

Quick search by object or event type is supported;

### Perimeter Protection

Human/Vehicle Analysis Up to 4-ch

### Facial Detection

Facial Detection and Capture Face picture detection, face picture search

### Recording

Video Compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264

### Video Bitrate

32 Kbps to 6Mbps

### Dual-stream

Support

### Stream Type

Video, Video & Audio

### Audio Compression

G.711u

### Audio Bitrate

64 Kbps

### Video and Audio

2-ch (up to 10-ch)

Up to 6 MP resolution Enhanced IP mode on:

4-ch (up to 12-ch), each up to 4 Mbps

### IP Video Input

Support H.265+/H.265/H.264+/H.264 IP cameras

### Analog Video Input

8-ch; BNC interface (1.0Vp-p, 75 Ω), supporting coaxitron connection

1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,

### HDMI Output

HDMI/VGA simultaneous output

### CVBS Input

PAL/NTSC

1-ch, BNC (1.0Vp-p, 75 Ω),

### CVBS Output

resolution: PAL: 704 × 576, NTSC: 704 × 480

### Synchronous playback

8-ch

3K(2960 × 1665)@20 fps, 5 MP(2560 × 1944)@20 fps,

### HDTVI Input

4 MP(2560 × 1440)@30 fps,

4MP(2560 × 1440)@25 fps, 1080p@30 fps,

1080p@25 fps, 720p@30 fps, 720p@25 fps

### VGA Output

1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz

---

	5 MP(2560 × 1944)@20 fps,4 MP(2560 × 1440)@30 fps,
<b>AHD Input</b>	4 MP(2560× 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30fps, 720p@25 fps
	5 MP(2592 × 1944)@20 fps,4 MP(2560 × 1440)@30 fps,
<b>HDCVI Input</b>	4 MP(2560× 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30fps, 720p@25 fps
<b>Audio Output</b>	1-ch, RCA (Linear, 1 KΩ)
<b>Audio Input</b>	1-ch, RCA (2.0 Vp-p,1 KΩ)‡8-ch via coaxialcable
<b>Two-Way Audio</b>	1-ch, RCA (2.0Vp-p, 1 KΩ) (using the first audioinput)
<b>Network</b>	
<b>Total Bandwidth</b>	96 Mbps
	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS,iSCSI, UPnP™, HTTPS,
<b>Network Protocol</b>	ONVIF
<b>Remote Connection</b>	64
<b>Network Interface</b>	1, RJ45 10M/100M self-adaptive Ethernet interface
<b>Auxiliary Interface</b>	
<b>SATA</b>	1 SATA interface
<b>Capacity</b>	Up to 10 TB capacity for each disk
<b>Serial Interface</b>	RS-485 (half-duplex)
<b>USB Interface</b>	2 × USB 2.0
<b>Alarm In/Out</b>	N/A
<b>General</b>	
<b>Power Supply</b>	12 VDC
<b>Consumption</b>	≤ 18 W
<b>Working Temperature</b>	-10 °C to +55°C (+14 °F to +131°F)
<b>Working Humidity</b>	10% to 90%
<b>Dimension (W × D × H)</b>	315 × 242 × 45 mm (12.4× 9.5 × 1.8 inch)
<b>Weight</b>	≤ 1.78 kg (3.9lb)