eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

HIKVISION

IDS-7208HQHI-M1/S

Kod: 00-00002599 · Videoregistrator



IDS-7208HQHI-M1/S AcuSense DIGITAL VIDEO RECORDER HIKVISION

Texniki göstəricilər

XVR	Növ
8 kanal	Kanal sayı
4 MP	Meqapixel
1 HDD	Max HDD sayı
10 TB	Max HDD həcmi

Ətraflı məlumat

Motion Detection 2.0	
Human/Vehicle Analysis	Deep learning-based motiondetection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights; Quick searchby object or event typeis supported;
Perimeter Protection	
Human/Vehicle Analysis	Up to 4-ch
Facial Detection	
Facial Detection and Capture	Face picture detection, face picture search
Recording	
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Video Bitrate	32 Kbps to 6Mbps
Dual-stream	Support
Stream Type	Video, Video& Audio
Audio Compression	G.711u
Audio Bitrate	64 Kbps
Video and Audio	
IP Video Input	2-ch (up to 10-ch) Up to 6 MP resolution Enhanced IP mode on: 4-ch (up to 12-ch), each up to 4 Mbps Support H.265+/H.265/H.264+/H.264 IP cameras
Analog VideoInput	8-ch;BNC interface (1.0Vp-p, 75 Ω), supporting coaxitron connection
HDMI Output	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz, HDMI/VGA simultaneous output
CVBS Input	PAL/NTSC

CVBS Output	1-ch, BNC (1.0Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC:704 × 480
Synchronous playback	8-ch
HDTVI Input	3K(2960 x 1665)@20 fps, 5 MP(2560× 1944)@20 fps, 4 MP(2560× 1440)@30 fps, 4MP(2560 × 1440)@25 fps,1080p@30 fps, 1080p@25 fps,720p@30 fps, 720p@25 fps
VGA Output	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz
AHD Input	5 MP(2560 × 1944)@20 fps,4 MP(2560 × 1440)@30 fps, 4 MP(2560× 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30fps, 720p@25 fps
HDCVI Input	5 MP(2592 × 1944)@20 fps,4 MP(2560 × 1440)@30 fps, 4 MP(2560× 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30fps, 720p@25 fps
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Audio Input	1-ch, RCA (2.0 Vp-p,1 KΩ)□ 8-ch via coaxialcable
Two-Way Audio	1-ch, RCA (2.0Vp-p, 1 KΩ) (using the first audioinput)
Network	
Total Bandwidth	96 Mbps
Network Protocol	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS,iSCSI, UPnP™, HTTPS, ONVIF
Remote Connection	64
Network Interface	1, RJ45 10M/100M self-adaptive Ethernet interface
Auxiliary Interface	
SATA	1 SATA interface
Capacity	Up to 10 TB capacity for each disk
Serial Interface	RS-485 (half-duplex)

USB Interface	2 × USB 2.0
Alarm In/Out	N/A
General	
Power Supply	12 VDC
Consumption	≤ 18 W
Working Temperature	-10 °C to +55°C (+14 °F to +131°F)
Working Humidity	10% to 90%
Dimension (W × D × H)	315 × 242 × 45 mm (12.4× 9.5 × 1.8 inch)
Weight	≤ 1.78 kg (3.9lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az