HIKVISION

iDS-7208HQHI-M1/XT

Kod: 00-00005708 · Videoregistrator



Hikvision iDS-7208HQHI-M1/XT 8-kanallı 1080p H.265 AcuSense DVR təhlükəsizliyi maksimum səviyyəyə çatdırır. Ağıllı hərəkət aşkarlama, 1 HDD dəstəyi və uzaqdan idarəetmə imkanları ilə kiçik və orta ölçülü obyektlər üçün ideal video nəzarət həllidir.

Texniki göstəricilər

XVR	Növ
8 kanal	Kanal sayı
5 MP	Meqapixel
1 HDD	Max HDD sayı
10 TB	Max HDD həcmi

Ətraflı məlumat

Category	Specification
Facial Recognition	Face picture library: up to 16 libraries Face picture comparison & search: 2-ch alarm for HD analog cameras
Motion Detection 2.0	Deep learning-based; human/vehicle classification; reduces false alarms; quick search by object/event type
Perimeter Protection	Human/vehicle analysis, up to 4-chNote: Face comparison, motion detection 2.0, and perimeter protection **cannot run simultaneously**
Video Input	IP: 4-ch (up to 12-ch), up to 6 MP Analog: 8-ch (BNC 1.0 Vp-p, 75 Ω, coaxitron supported) HDTVI: 3K/2K/5 MP/4 MP/1080p/720p, various fps AHD: 5 MP/4 MP/1080p/720p, various fps HDCVI: 3K/5 MP/4 MP/1080p/720p, various fps CVBS: PAL/NTSC
Video Output	HDMI: 1-ch, 1080p/60Hz, 1280×1024/60Hz, 1280×720/60Hz, simultaneous HDMI/VGA VGA: 1-ch, 1080p/60Hz, 1280×1024/60Hz, 1280×720/60Hz, simultaneous HDMI/VGA CVBS: 1-ch, PAL 704×576, NTSC 704×480
Audio	Input: 8-ch RCA (2.0 Vp-p, 1 KΩ), 8-ch via coaxial cable; optional up to 8-chOutput: 1-ch RCA Linear 1 KΩ Two-way: 1-ch via first input Compression: G.711u, Bitrate: 64 Kbps
Recording	Video compression: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 Encoding resolution: 3K lite/5 MP lite/4 MP lite/1080p/720p/VGA/WD1/4CIF/CIF (1080p Lite mode available) Frame rate: Main stream varies 12–30 fps depending on resolution, Sub-stream WD1/4CIF@12fps, CIF@25/30fps Video bitrate: 32 Kbps to 6 Mbps Dual-stream: main/sub-stream support

Category	Specification
Synchronous Playback	8-ch
Network	Remote connection: 64Total bandwidth: 96 Mbps Protocols: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF, ISUP Interface: 1 × RJ45 10/100 Mbps Wi-Fi: Connectable via USB dongle
Storage & Interfaces	SATA: 1 × interface, up to 10 TB per disk Serial: RS-485 (half-duplex)USB: Front 1 × USB 2.0, Rear 1 × USB 2.0Alarm In/Out: 8/4; optional 4/1
General	Power supply: 12 VDC, 1.5 A Consumption: ≤ 18 W (without HDD) Working temp: -10 °C to 55 °C Working humidity: 10–90 % Dimensions (W × D × H): 319 × 236 × 48 mm (12.6 × 9.3 × 1.9 in) Weight: ≤ 1.78 kg (without HDD)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az