

IDS-7208HQHI-M2/S/8

IDS-7208HQHI-M2/S/8AUDIO HD TVI DIGITAL VIDEO RECORDER HIKVISION



Specifications

Model	IDS-7208HQHI-M2/S/8
Brand	Hikvision
Növ	XVR
Kanal say?	8 kanal
Meqapixel	4 MP
Max HDD say?	2 HDD
Max HDD h?cmi	10 TB

KEY FEATURES

Motion Detection 2.0

Human/Vehicle Analysis

Deep learning-based motiondetection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leavesand lights;

Quick searchby object or event typeis supported;

Perimeter Protection

Human/Vehicle Analysis

Up to 4-ch

Facial Detection

Facial Detection and CaptureFace picturedetection, face picturesearch

Recording

Video Compression

H.265 Pro+/H.265 Pro/H.265/H.264+/H.264

When 1080p Litemode is not enabled:

3K lite/5 MP lite/4 MP lite

Encoding Resolution

/1080p/720p/VGA/WD1/4CIF/CIF;

When1080p Lite modeis enabled:

3K lite/5 MP lite/4MP lite/1080p lite/720p lite/VGA/WD1/4CIF/CIF

Main stream:

When 1080pLite mode not enabled:

For 3K stream access: 3Klite@12fps;4 MP lite/1080p@15fps;720p/WD1/4CIF/VGA/CIF@20fps

For 5 MP stream access: 5 MP lite@12fps;4 MP lite/1080p@15fps;720p/WD1/4CIF/VGA/CIF@20fps

For 4 MP stream access:4 MP lite/1080p@15fps;720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N)

For 1080p stream access: 1080p/720p@15fps; VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) For 720p stream access: 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)

When 1080p Lite mode enabled:

3K lite/5 MP lite@12fps;4 MP lite@15fps;1080p lite/720p lite/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)

Sub-stream:

Frame Rate

WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)

Video Bitrate

32 Kbps to 6 Mbps

Dual-stream

Support

Stream Type

Video, Video& Audio

Audio Compression

G.711u

Audio Bitrate

64 Kbps

Video and Audio

	2-ch (upto 10-ch)
	Up to 6 MP resolution Enhanced IP mode on:
	4-ch (up to 12-ch),each up to 4 Mbps;
IP Video Input	Support H.265+/H.265/H.264+/H.264 IP cameras
	8-ch;
Analog VideoInput	BNC interface (1.0 Vp-p,75 Ω), supporting coaxitron connection
	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,
HDMI Output	HDMI/VGA simultaneous output
VGA Output	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
CVBS Input	PAL/NTSC
	1-ch, BNC (1.0Vp-p, 75 Ω),
CVBS Output	resolution: PAL: 704 × 576, NTSC:704 × 480
Synchronous playback	8-ch
	3K(2960 x 1665)@20 fps, 5 MP(2560× 1944)@20 fps,
HDTVl Input	4 MP(2560× 1440)@30 fps, 4
	MP(2560 × 1440)@25 fps,
	1080p@30 fps, 1080p@25 fps,
	720p@30 fps, 720p@25 fps
	5 MP(2560 × 1944)@20fps,4 MP(2560 × 1440)@30 fps,
AHD Input	4 MP(2560× 1440)@25 fps,
	1080p@30 fps, 1080p@25 fps,720p@30 fps, 720p@25fps
	5 MP(2592 × 1944)@20 fps,4MP(2560 × 1440)@30 fps,
HDCVI Input	4 MP(2560× 1440)@25 fps,
	1080p@30 fps,1080p@25 fps, 720p@30fps, 720p@25 fps
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Audio Input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (usingthe first audioinput)
Network	
Total Bandwidth	96 Mbps
	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS,
Network Protocol	ONVIF
Remote Connection	64
Network Interface	1, RJ45 10M/100M self-adaptive Ethernet interface
Auxiliary Interface	
SATA	2 SATA interface © 2026 Hikvision. All rights reserved. Eurotechnology
Capacity	Up to 10 TBcapacity for each disk