

IDS-7208HQHI-M2/S/8

IDS-7208HQHI-M2/S/8AUDIO HD TVI DIGITAL VIDEO RECORDER HIKVISION



Model	IDS-7208HQHI-M2/S/8
Brend	Hikvision
Növ	XVR
Kanal sayı	8 kanal
Meqapixel	4 MP
Max HDD sayı	2 HDD
Max HDD həcmi	10 TB

Specification

Motion Detection 2.0	
Human/Vehicle Analysis	Deep learning-based motiondetection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leavesand lights; Quick searchby object or event typeis supported;
Perimeter Protection	
Human/Vehicle Analysis	Up to 4-ch
Facial Detection	
Facial Detection and Capture	Face picturedetection, face picturesearch
Recording	
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding Resolution	When 1080p Litemode is not enabled: 3K lite/5 MP lite/4 MP lite /1080p/720p/VGA/WD1/4CIF/CIF; When1080p Lite modeis enabled: 3K lite/5 MP lite/4MP lite/1080p lite/720p lite/VGA/WD1/4CIF/CIF

Frame Rate	<p>Main stream:</p> <p>When 1080p Lite mode not enabled:</p> <p>For 3K stream access: 3K lite@12fps; 4 MP lite/1080p@15fps; 720p/WD1/4CIF/VGA/CIF@20fps</p> <p>For 5 MP stream access: 5 MP lite@12fps; 4 MP lite/1080p@15fps; 720p/WD1/4CIF/VGA/CIF@20fps</p> <p>For 4 MP stream access: 4 MP lite/1080p@15fps; 720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N)</p> <p>For 1080p stream access: 1080p/720p@15fps; VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) For 720p stream access: 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)</p> <p>When 1080p Lite mode enabled:</p> <p>3K lite/5 MP lite@12fps; 4 MP lite@15fps; 1080p lite/720p lite/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)</p> <p>Sub-stream:</p> <p>WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)</p>
Video Bitrate	32 Kbps to 6 Mbps
Dual-stream	Support
Stream Type	Video, Video& Audio
Audio Compression	G.711u
Audio Bitrate	64 Kbps
Video and Audio	
IP Video Input	<p>2-ch (upto 10-ch)</p> <p>Up to 6 MP resolution Enhanced IP mode on:</p> <p>4-ch (up to 12-ch), each up to 4 Mbps;</p> <p>Support H.265+/H.265/H.264+/H.264 IP cameras</p>
Analog Video Input	<p>8-ch;</p> <p>BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection</p>
HDMI Output	<p>1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,</p> <p>HDMI/VGA simultaneous output</p>
VGA Output	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
CVBS Input	PAL/NTSC
CVBS Output	<p>1-ch, BNC (1.0Vp-p, 75 Ω),</p> <p>resolution: PAL: 704 × 576, NTSC: 704 × 480</p>
Synchronous playback	8-ch
HDTVI Input	<p>3K(2960 x 1665)@20 fps, 5 MP(2560 × 1944)@20 fps,</p> <p>4 MP(2560 × 1440)@30 fps, 4</p> <p>MP(2560 × 1440)@25 fps,</p> <p>1080p@30 fps, 1080p@25 fps,</p> <p>720p@30 fps, 720p@25 fps</p>
AHD Input	<p>5 MP(2560 × 1944)@20fps, 4 MP(2560 × 1440)@30 fps,</p> <p>4 MP(2560 × 1440)@25 fps,</p> <p>1080p@30 fps, 1080p@25 fps, 720p@30 fps, 720p@25fps</p>

HDCVI Input	5 MP(2592 × 1944)@20 fps,4MP(2560 × 1440)@30 fps, 4 MP(2560× 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30fps, 720p@25 fps
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Audio Input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (usingthe first audioinput)
Network	
Total Bandwidth	96 Mbps
Network Protocol	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
Remote Connection	64
Network Interface	1, RJ45 10M/100M self-adaptive Ethernet interface
Auxiliary Interface	
SATA	2 SATA interface
Capacity	Up to 10 TBcapacity for each disk
Serial Interface	RS-485 (half-duplex)
USB Interface	Front panel: 1 × USB 2.0; Rear panel:1 × USB 2.0
Alarm In/Out	N/A
General	
Power Supply	12 VDC
Consumption	≤ 30 W
Working Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	380 × 320 × 48 mm (15.0 × 12.6 × 1.9 inch)
Weight	≤ 1.78 kg (3.9 lb)