eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

HIKVISION

IDS-7216HQHI-M1/S

Kod: 00-00000538 · Videoregistrator



IDS-7216HQHI-M1/S AcuSense DIGITAL VIDEO RECORDER HIKVISION

Texniki göstəricilər

XVR Növ	**16 kanal** Kanal sayı
5 MP Meqapixel	**1 HDD** Max HDD sayı
10 TB Max HDD həcmi	

Ətraflı məlumat

Motion Detection 2.0	
Human/Vehicle Analysis	Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights; Quick searchby object or event typeis supported;
Perimeter Protection	
Human/Vehicle Analysis	Up to 4-ch
Facial Detection	
Facial Detection and Capture	Face picturedetection, face picturesearch
Recording	
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding Resolution	When 1080p Litemode is not enabled: 3K lite/5 MP lite/4 MP lite/1080p/720p/VGA/WD1/4CIF/CIF; When1080p Lite modeis enabled: 3K lite/5 MP lite/4MP lite/1080p lite/720p lite/VGA/WD1/4CIF/CIF
Video Bitrate	32 Kbps to 6 Mbps
Dual-stream	Support
Stream Type	Video, Video& Audio
Audio Compression	G.711u
Audio Bitrate	64 Kbps

Video and Audio	
IP Video Input	2-ch (upto 18-ch) Up to 6 MP resolution Enhanced IP mode on: 8-ch (up to 24-ch),each up to 4 Mbps ;Support H.265+/H.265/H.264+/H.264 IP cameras
Analog VideoInput	16-ch;BNC interface (1.0Vp-p, 75 Ω), supporting coaxitron connection

HDMI Output	1-ch, 4K (3840× 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280× 720/60Hz
VGA Output	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280 ×720/60Hz
CVBS Input	PAL/NTSC
CVBS Output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC:704 × 480
Synchronous playback	16-ch
HDTVI Input	3K(2960 x 1665)@20 fps, 5 MP(2560× 1944)@20 fps, 4 MP(2560× 1440)@30 fps, 4 MP(2560 × 1440)@25 fps,1080p@30 fps, 1080p@25 fps, 720p@30 fps, 720p@25 fps
AHD Input	5 MP(2592 × 1944)@20 fps,4MP(2560 × 1440)@30 fps, 4 MP(2560× 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30fps, 720p@25 fps
HDCVI Input	5 MP(2592 × 1944)@20 fps,4MP(2560 × 1440)@30 fps, 4 MP(2560× 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30fps, 720p@25 fps
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Audio Input	1-ch, RCA (2.0 Vp-p, 1 KΩ) 16-ch via coaxialcable
Audio Input	1
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (usingthe first audioinput)
Network	
Total Bandwidth	128 Mbps
Network Protocol	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
Remote Connection	128

Network Interface	1,RJ45 10M/100M/1000M self-adaptive Ethernet interface
Auxiliary Interface	
SATA	1 SATA interface
Capacity	Up to 10 TBcapacity for each disk
Serial Interface	RS-485 (half-duplex)

USB Interface	1 × USB 2.0 1 × USB 3.0
Alarm In/Out	N/A
General	
Power Supply	12 VDC
Consumption	≤ 24 W
Working Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	315 × 242 × 45 mm (12.4 × 9.5 × 1.8 inch)
Weight	≤ 2 kg (4.4 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az