HIKVISION

iDS-7216HQHI-M1/XT

Kod: 00-00005365 · Videoregistrator



Hikvision iDS-7216HQHI-M1/XT 16-kanallı 1080p DVR H.265 və AcuSense texnologiyası ilə təchiz olunub. Hərəkət aşkarlanması, yüksək keyfiyyətli qeyd, uzaqdan idarəetmə və etibarlı təhlükəsizlik üçün ideal həll təqdim edir.

Texniki göstəricilər

XVR	**16 kanal**
Növ	Kanal sayı
5 MP	**1 HDD**
Meqapixel	Max HDD sayı
12 TB	
Max HDD həcmi	

Ətraflı məlumat

Category	Specification
Facial Recognition	Face picture comparison and search (4-ch comparison for HD analog cameras)
Face Picture Library	Up to 16 libraries; HDD damage won’t cause data loss (backup on HDD & flash)
Motion Detection 2.0	Human/Vehicle analysis using deep learning; reduces false alarms; quick search by object/event
Perimeter Protection	Human/Vehicle analysis up to 8-ch (advanced model)
Facial Detection	Face detection and capture, 4-ch capture
Video Input	IP: 8-ch (up to 24-ch) up to 6 MP resolution Analog: 16-ch (BNC, 1.0 Vp-p, 75 Ω, coaxitron supported) HDTVI: 3K/2K/5 MP/4 MP/1080P/720P at specified fpsAHD: 5 MP/4 MP/1080P/720P at specified fpsHDCVI: 3K/5 MP/4 MP/1080P/720P at specified fpsCVBS: PAL/NTSC
Video Output	HDMI: 1-ch, 4K/30Hz, 2K/60Hz, 1080p/60Hz, 1280×1024/60Hz, 1280×720/60Hz, HDMI/VGA simultaneous output VGA: 1-ch, 1080p/60Hz, 1280×1024/60Hz, 1280×720/60Hz, HDMI/VGA simultaneous output
Audio	Input: 1-ch (up to 16 optional), RCA 2.0 Vp-p, 1 KΩ, 16-ch via coaxOutput: 1-ch, RCA Linear 1 KΩTwo-way: 1-ch, RCA 2.0 Vp-p using first input Compression: G.711u, Bitrate: 64 Kbps
Recording	Video compression: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 Encoding resolution: 2K/3K lite/5 MP lite/4 MP lite/1080p/720p/VGA/WD1/4CIF/CIF, with 1080p Lite mode option Frame rate: See detailed specs per resolution and Lite modeVideo bitrate: 32 Kbps to 6 MbpsDual-stream: main/sub-stream support
Decoding	Up to 24-ch 1080P@30fps

Category	Specification
Network	Remote connection: 128Total bandwidth: 256 Mbps Protocols: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF, ISUP Interface: 1 × RJ45 10/100/1000 Mbps
Storage & Interfaces	SATA: 1 × interface, up to 12 TB per disk Serial: RS-485 (half-duplex)USB: Front: 1 × USB 2.0, Rear: 2 × USB 3.0Alarm: Optional
General	Power: 12 VDC, 2 AConsumption: ≤ 24 W Working temperature: -10 °C to 55 °C (14 °F to 131 °F) Working humidity: 10–90 % Dimensions (W × D × H): 319 × 240 × 48 mm (12.6 × 9.4 × 1.9 in) Weight: ≤ 2 kg (4.4 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az