

HIKVISION

iDS-7216HQHI-M1/XT

Kod: 00-00005365 · Videoregistrator



Hikvision iDS-7216HQHI-M1/XT 16-kanallı 1080p DVR H.265 və AcuSense texnologiyası ilə təchiz olunub. Hərəkət aşkarlanması, yüksək keyfiyyətli qeyd, uzaqdan idarəetmə və etibarlı təhlükəsizlik üçün ideal həll təqdim edir.

Texniki göstəricilər



XVR

Növ



16 kanal

Kanal sayı



5 MP

Məqapixel



1 HDD

Max HDD sayı



12 TB

Max HDD həcmi

Ətraflı məlumat

Category	Specification
Facial Recognition	Face picture comparison and search (4-ch comparison for HD analog cameras)
Face Picture Library	Up to 16 libraries; HDD damage won't cause data loss (backup on HDD & flash)
Motion Detection 2.0	Human/Vehicle analysis using deep learning; reduces false alarms; quick search by object/event
Perimeter Protection	Human/Vehicle analysis up to 8-ch (advanced model)
Facial Detection	Face detection and capture, 4-ch capture
Video Input	IP: 8-ch (up to 24-ch) up to 6 MP resolution Analog: 16-ch (BNC, 1.0 Vp-p, 75 Ω, coaxitron supported) HDTV: 3K/2K/5 MP/4 MP/1080P/720P at specified fps AHD: 5 MP/4 MP/1080P/720P at specified fps HDCVI: 3K/5 MP/4 MP/1080P/720P at specified fps CVBS: PAL/NTSC
Video Output	HDMI: 1-ch, 4K/30Hz, 2K/60Hz, 1080p/60Hz, 1280×1024/60Hz, 1280×720/60Hz, HDMI/VGA simultaneous output VGA: 1-ch, 1080p/60Hz, 1280×1024/60Hz, 1280×720/60Hz, HDMI/VGA simultaneous output
Audio	Input: 1-ch (up to 16 optional), RCA 2.0 Vp-p, 1 KΩ, 16-ch via coax Output: 1-ch, RCA Linear 1 KΩ Two-way: 1-ch, RCA 2.0 Vp-p using first input Compression: G.711u, Bitrate: 64 Kbps
Recording	Video compression: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 Encoding resolution: 2K/3K lite/5 MP lite/4 MP lite/1080p/720p/VGA/WD1/4CIF/CIF, with 1080p Lite mode option Frame rate: See detailed specs per resolution and Lite mode Video bitrate: 32 Kbps to 6 Mbps Dual-stream: main/sub-stream support
Decoding	Up to 24-ch 1080P@30fps

Category	Specification
Network	Remote connection: 128 Total bandwidth: 256 Mbps Protocols: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF, ISUP Interface: 1 × RJ45 10/100/1000 Mbps
Storage & Interfaces	SATA: 1 × interface, up to 12 TB per disk Serial: RS-485 (half-duplex) USB: Front: 1 × USB 2.0, Rear: 2 × USB 3.0 Alarm: Optional
General	Power: 12 VDC, 2 A Consumption: ≤ 24 W Working temperature: -10 °C to 55 °C (14 °F to 131 °F) Working humidity: 10-90 % Dimensions (W × D × H): 319 × 240 × 48 mm (12.6 × 9.4 × 1.9 in) Weight: ≤ 2 kg (4.4 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az