

IDS-7232HQHI-M2/S

NVR for IP Cameras



Specifications

Model	IDS-7232HQHI-M2/S
Brand	Hikvision
Növ	XVR
Kanal say?	32 kanal
Meqapixel	4 MP
Max HDD say?	2 HDD
Max HDD h?cmi	10 TB

KEY FEATURES

Model	iDS-7216HQHI-M2/S
Motion Detection 2.0 ¹	<p>Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;</p>
Human/Vehicle Analysis	Quick search by object or event type is supported;
Perimeter Protection ¹	
Human/Vehicle Analysis	Up to 4-ch
Recording	
Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
	<p>Main stream:</p> <p>When 1080p Lite mode not enabled:</p> <p>For 4 MP stream access:</p> <p>4 MP lite@15 fps;</p> <p>1080p lite/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30fps (N) For 3MP stream access: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF@15 fps</p> <p>For 1080p stream access:</p> <p>1080p/720p@15 fps;VGA/WD1/4CIF/CIF@25 fps (P)/30fps (N)</p> <p>For 720p stream access: 720p/VGA/WD1/4CIF/CIF@25 fps (P)/30 fps</p> <p>(N) When 1080p Lite mode enabled:</p> <p>4 MP lite/3 MP@15 fps;</p> <p>1080p lite/720p lite/VGA/WD1/4CIF/CIF@25 fps(P)/30 fps</p> <p>(N)</p> <p>Sub-stream:</p> <p>WD1/4CIF@12 fps; CIF@25 fps (P)/30 fps (N)</p>
Encoding resolution	
Video bitrate	32 Kbps to 6 Mbps
Dual stream	Support
Stream type	Video, Video & Audio
Audio compression	G.711u
Audio bitrate	64 Kbps
Video and Audio	

	2-ch (upto 18-ch)	
	Enhanced IP mode on:	
IP video input2	8-ch (up to 24-ch),each up to 4 Mbps	
	Up to 6 MP resolution	
	Support H.265+/H.265/H.264+/H.264 IP cameras	
	16-ch	
Analog videoinput	BNC interface (1.0Vp-p, 75 Ω), supporting coaxitron connection	
HDTVl input	3K@20 fps, 4 MP@30 fps, 4 MP@25 fps, 3 MP@18 fps, 1080p@30 fps, 1080p@25 fps,720p@60 fps, 720p@50 fps, 720p@30 fps, 720p@25 fps	
	*: The 3 MP signal input is only available for channel 1/2 of iDS-7208HQHI-M2/S, and for channel 1/2/3/4of iDS-7216HQHI-M2/S.	
AHD input	4 MP@25 fps, 4MP@30 fps, 1080p@25 fps, 1080p@30 fps, 720p@25 fps, 720p@30 fps	
HDCVl input	4 MP@25 fps, 4 MP@30fps, 1080p@25 fps, 1080p@30 fps, 720p@25fps, 720p@30 fps	
CVBS input	PAL/NTSC	
	1-ch, BNC (1.0Vp-p, 75 Ω),	
CVBS output	resolution: PAL:704 × 576,NTSC: 704 × 480	
HDMI output	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz	
VGA output	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz	
Video outputmode	HDMI/VGA simultaneous output	
Audio input3	1-ch (up to 8-ch is optional), RCA (2.0 Vp-p, 1 KΩ)	1-ch (up to 16-chis optional), RCA (2.0 Vp-p, 1 KΩ)
	8-ch via coaxial cable	16-ch via coaxial cable
Audio output	1-ch, RCA (Linear, 1 KΩ)	
Two-way audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (usingthe first audioinput)	
Synchronous playback	8-ch	16-ch
Network		
Remote connection	64	128
	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS,	
Network protocol	ONVIF	