

IDS-7232HQHI-M2/XT

Hikvision IDS-7232HQHI-M2/XT – 32 kanallı 1080P HD DVR cihazıdır. AcuSense texnologiyası ilə insan və nəqliyyat vasitəsini ağıllı şəkildə tanıyır. H.265 video sıxılma formatı ilə yaddaşdan maksimum səmərə əldə edilir. Təhlükəsizlik sistemləri üçün etibarlı və güclü həll.



Specifications

Model	IDS-7232HQHI-M2/XT
Brand	Hikvision
Növ	XVR
Kanal say?	32 kanal
Max HDD say?	2 HDD
Meqapixel	4 MP
Max HDD həcmi	12 TB

KEY FEATURES

Category	Specification
Model	iDS-7232HQHI-M2/XT
Type	32-ch 1080P 1U H.265 AcuSense DVR
Main Features	32 channels, 2 HDD, supports 4-ch facial recognition or 8-ch perimeter protection, H.265 Pro+, 5 signals (HDTVI/AHD/CVI/CVBS/IP), up to 40 IP channels (6MP each), 24×1080P decoding
Facial Recognition	Up to 16 face libraries; 4-ch face comparison alarm (HD analog)
Perimeter Protection	Up to 8-ch (advanced model), Human/Vehicle Analysis
Motion Detection 2.0	Deep learning-based, Human/Vehicle classification
Analog Video Input	32-ch BNC (1.0 Vp-p, 75Ω)
IP Video Input	8-ch (up to 40-ch total), each up to 6MP
HDMI Output	1-ch, up to 4K (3840×2160)/30Hz
VGA Output	1-ch, up to 1920×1080/60Hz
CVBS Output	1-ch BNC, PAL: 704×576 / NTSC: 704×480
Synchronous Playback	16-ch
HDTVI Input	Up to 5MP@20fps, 4MP@25/30fps, 1080P@25/30fps, 720P@25/30fps
AHD Input	Up to 5MP@20fps, 4MP@25/30fps, 1080P@25/30fps, 720P@25/30fps
HDCVI Input	Up to 5MP@20fps, 4MP@25/30fps, 1080P@25/30fps, 720P@25/30fps
Audio Input	1-ch RCA (2.0 Vp-p, 1KΩ), 32-ch via coax
Audio Output	1-ch RCA (1KΩ)
Two-Way Audio	1-ch RCA (using audio input)
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Audio Compression	G.711u
Video Bitrate	32 Kbps – 10 Mbps
Audio Bitrate	64 Kbps
Encoding Resolution	3K Lite / 5MP Lite / 4MP Lite / 1080P / 720P / VGA / WD1 / 4CIF / CIF
Frame Rate (Main Stream)	Up to 25/30fps depending on mode
Sub Stream	WD1/4CIF@12fps, CIF@25/30fps
Decoding Capability	Up to 24-ch 1080P@30fps
Network Bandwidth	256 Mbps total
Network Interface	1 × RJ45 10/100/1000 Mbps
Protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF, ISUP
Remote Connections	128
SATA Interfaces	2 × SATA, up to 12 TB each
USB Interfaces	Front: 1 × USB 2.0, Rear: 2 × USB 3.0
RS-485	1 (half-duplex)
Alarm I/O	Optional
Power Supply	12 VDC, 5 A
Power Consumption	≤ 60 W
Operating Temperature	-10 °C to +55 °C
Humidity	10% – 90%

Category		Specification
Dimensions (W×D×H)	384 × 313 × 52 mm	
Weight	≤ 2.1 kg	
Available Model	iDS-7232HQHI-M2/XT	