

**CUDY****IG1005P**

Kod: 00-00005587 · Switchlər



CUDY IG1005P 5-Port Gigabit Industrial PoE+ switch sənaye mühitləri üçün hazırlanmış etibarlı şəbəkə həlldir. PoE+ dəstəyi ilə IP kameralar və access pointləri enerji ilə təmin edir. Geniş temperatur aralığı və metal korpusu sayəsində zavod, anbar və açıq sahələrdə stabil işləyir.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](#)<https://eurotechnology.az/product/cudy/ig1005p>**Texniki göstəricilər****5 Port**

Port sayı

**PoE+**

PoE

**120 W**

PoE gücü

**1000mb/s**

Port sürəti

**Ətraflı məlumat**

|                                       |                                                                                                                                                                                                                                                                                 |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Model</b>                          | IG1005P 2.0                                                                                                                                                                                                                                                                     |
| <b>Gigabit RJ45 Ports</b>             | 5                                                                                                                                                                                                                                                                               |
| <b>Gigabit RJ45 PoE Ports</b>         | #1~#4                                                                                                                                                                                                                                                                           |
| <b>Max Power on a Single PoE Port</b> | 30W                                                                                                                                                                                                                                                                             |
| <b>PoE Port Notes</b>                 | The PoE ports comply with IEEE 802.3at/af standards.                                                                                                                                                                                                                            |
| <b>Shielded RJ45 Port</b>             | True                                                                                                                                                                                                                                                                            |
| <b>Extend Mode Ports</b>              | #1~#4                                                                                                                                                                                                                                                                           |
| <b>VLAN Mode Ports</b>                | #1~#4                                                                                                                                                                                                                                                                           |
| <b>LED</b>                            | <ul style="list-style-type: none"> <li>• Power 1</li> <li>• Power 2</li> <li>• Link/ACT of Each Ethernet Port</li> <li>• PoE Status of Each PoE Port</li> </ul>                                                                                                                 |
| <b>Power Interfaces</b>               | Power Input Terminal                                                                                                                                                                                                                                                            |
| <b>Physical Buttons</b>               | <ul style="list-style-type: none"> <li>• PoE Watchdog On/Off</li> <li>• VLAN On/Off</li> <li>• Extend On/Off</li> <li>• Broadcast Storm Prevention On/Off</li> </ul>                                                                                                            |
| <b>Physical Buttons Note</b>          | <p>The PoE Watchdog will attempt to reboot the plugged-in clients that have been inactive for 5 minutes.</p> <p>Do not turn it on for clients with online auto-upgrade feature.</p>                                                                                             |
| <b>Copper Speed and Distance</b>      | <ul style="list-style-type: none"> <li>• Cat. 3 or higher cable: 100 meters at 10 Mbps</li> <li>• Cat. 5 or higher cable: 100 meters at 100 Mbps</li> <li>• Cat. 5e or higher cable: 100 meters at Gigabit</li> <li>• Cat. 5e or higher cable: 250 meters at 10 Mbps</li> </ul> |
| <b>Copper Speed and Distance Note</b> | 250-meter transmission is only available on the Extend Mode ports when the Extend Mode is activated.                                                                                                                                                                            |
| <b>MAC Address Table</b>              | 2048                                                                                                                                                                                                                                                                            |
| <b>Max Switching Capacity</b>         | 10 Gbps                                                                                                                                                                                                                                                                         |

|                                    |                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Max Forwarding Rate</b>         | 7.44 Mpps                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Jumbo Frame</b>                 | 2 KB                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Packet Buffer</b>               | 2 Mbit                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Power Methods</b>               | DC via Terminal Block                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Power Redundancy</b>            | Dual Inputs                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Power Input</b>                 | 44-57V□                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Max Power Consumption</b>       | 120W                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Max Power Excluding PoE</b>     | 2.0W                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Idle Power Consumption</b>      | 1.4W                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Polarity Reverse Protection</b> | True                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Short Circuit Protection</b>    | True                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>802.3 Protocols</b>             | <ul style="list-style-type: none"> <li>• 802.3at PoE</li> <li>• 802.3af PoE</li> <li>• 802.3i 10BASE-T</li> <li>• 802.3u 100BASE-TX</li> <li>• 802.3ab 1000BASE-T</li> <li>• 802.3x Flow Control</li> </ul>                                                                                                                                                                                |
| <b>Grounding Methods</b>           | Grounding Point                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Safety</b>                      | IEC/EN 62368                                                                                                                                                                                                                                                                                                                                                                               |
| <b>EMC</b>                         | EN55032 Class A<br>EN55035 Class A                                                                                                                                                                                                                                                                                                                                                         |
| <b>EMI</b>                         | FCC 47 CFR Part 15B Class A                                                                                                                                                                                                                                                                                                                                                                |
| <b>EMS</b>                         | IEC/EN 61000-4-2, Level 4 ESD: Contact: 8kV; Air: 15kV<br>IEC/EN 61000-4-3, Level 4 RS: 80 MHz to 1 GHz: 30 V/m<br>IEC/EN 61000-4-4, Level 4 EFT: Power: 2kV; RJ45: 4kV<br>IEC/EN 61000-4-5, Level 4 Surge: Power: DM 2kV, CM 4kV; RJ45: CM 6kV<br>IEC/EN 61000-4-6, Level 3 CS: 10V<br>IEC/EN 61000-4-8, Level 5 PFMF<br>IEC/EN 61000-4-9, Level 5 PMF<br>IEC/EN 61000-4-10, Level 5 DOMF |
| <b>EMS Note</b>                    | The levels listed in each EMS field are the highest level defined in the IEC/EN standard.                                                                                                                                                                                                                                                                                                  |

|                                                                                           |                                                                                                                                                                                                              |
|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Shock</b>                                                                              | IEC 60068-2-27                                                                                                                                                                                               |
| <b>Vibration</b>                                                                          | IEC 60068-2-6                                                                                                                                                                                                |
| <b>Free Fall</b>                                                                          | IEC 60068-2-32                                                                                                                                                                                               |
| <b>Environment</b>                                                                        | Operating Temperature: -40 °C ~ 75 °C (-40 °F ~ 167 °F)<br>Storage Temperature: -40 °C ~ 85 °C (-40 °F ~ 185 °F)<br>Operating Humidity: 5% ~ 95% non-condensing<br>Storage Humidity: 5% ~ 95% non-condensing |
| <b>Dimension</b>                                                                          | Device:<br>33.5×86×118 mm<br>1.32×3.39×4.65 inches<br>Mounting Space:<br>33.5×130×138 mm<br>1.32×5.12×5.43 inches                                                                                            |
| <b>Product Weight</b>                                                                     | 342.5 g (12.08 oz.)                                                                                                                                                                                          |
| <b>Casing Material</b>                                                                    | Aluminum                                                                                                                                                                                                     |
| <b>Ingress Protection</b>                                                                 | IP40                                                                                                                                                                                                         |
| <b>Installation</b>                                                                       | DIN-Rail                                                                                                                                                                                                     |
| <ul style="list-style-type: none"> <li>• IG1005P</li> <li>• Installation Guide</li> </ul> |                                                                                                                                                                                                              |
| <b>Retail Package Dimension</b>                                                           | 182×137×65 mm<br>7.17×5.39×2.56 inches                                                                                                                                                                       |
| <b>Retail Package Weight</b>                                                              | 474.0 g (16.72 oz.)                                                                                                                                                                                          |
| <b>Units per Carton</b>                                                                   | 20                                                                                                                                                                                                           |
| <b>Carton Net Weight</b>                                                                  | 9.5 kg (20.94 lbs)                                                                                                                                                                                           |
| <b>Carton Gross Weight</b>                                                                | 10.1 kg (22.27 lbs)                                                                                                                                                                                          |
| <b>Carton Dimension</b>                                                                   | 38.8×34.8×29.8 cm<br>15.28×13.7×11.73 inches                                                                                                                                                                 |

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · [sales@eurotech.az](mailto:sales@eurotech.az)