

IPC-B122-APF28-ECO

IPC B122-APF28-ECO 2MP 2.8MM IR 30M,128GB Micro SD card ,Built-in Mic Bullet Network Kamera UNIARC



Specifications

Model	IPC-B122-APF28-ECO
Brand	Uniview
?? mühiti	Outdoor
Növ	IP
Meqapixel	2 MP
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
???qland?rma	IR
???qland?rma m?saf?si	30 m
Qoruma	IP67
Material	Plastik

KEY FEATURES

IPC-B122-APF28

Camera

Sensor 1/2.8", progressive scan, CMOS

Lens 2.8mm@F2.1

DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)
	2.8	43.4	17.4	8.7
	4.0	62.1	24.8	12.4

Angle of View (H) 106.7°

Angle of View (V) 57.1°

Angle of View (O) 115.7°

Adjustment angle Pan: 0° ~ 360° Tilt: 0° ~ 90°

Shutter Auto/Manual, 1 ~ 1/100000s

Minimum Illumination Colour: 0.02Lux (F2.1, AGC ON)
0Lux with IR on

Digital noise reduction 2D/3D DNR

Day/Night IR-cut filter with auto switch (ICR)

S/N >52dB

IR Range Up to 30m (98ft) IR range

Defog Digital Defog

WDR DWDR

Audio

Audio Compression G.711

Suppression Supported

Sampling Rate 8KHZ

Video

Video Compression Ultra 265, H.265, H.264

H.264 code profile Baseline profile, Main profile, High profile

Frame Rate Main Stream: 1080P (1920*1080), Max 25fps; 720P (1280*720), Max 25fps;
Sub Stream: D1 (720*576), Max 25fps; 640*360, Max 25fps; 2CIF(704*288), Max 25fps; CIF(352*288), Max 25fps;

HLC Supported

BLC Supported

OSD Up to 4 OSDs

Privacy Mask Up to 4 areas

ROI Up to 8 areas

Motion Detection Up to 4 areas

Network

Protocols IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP, RTMP

Compatible Integration ONVIF (Profile S, Profile T), API

Interface

Network 10/100M Base-TX Ethernet

Built-in Mic Supported

General

Power	DC 12V±25%, PoE Power consumption: Max 3.5W
Dimensions (L × W × H)	144 × 60 × 65mm (5.6" × 2.4" × 2.6")
Weight	0.17kg (0.37lb)
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	4KV
Ingress Protection	IP67
Reset Button	N/A