

IPC-B122-APF28-ECO

IPC B122-APF28-ECO 2MP 2.8MM IR 30M,128GB Micro SD card ,Built-in Mic Bullet Network Kamera UNIARC

Model	IPC-B122-APF28-ECO
Brend	Uniview
İş mühiti	Outdoor
Növ	IP
Meqapixel	2 MP
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR
İşıqlandırma məsafəsi	30 m
Qoruma	IP67
Material	Plastik



Specification

	IPC-B122-APF28			
Camera				
Sensor	1/2.8", progressive scan, CMOS			
Lens	2.8mm@F2.1			
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)
	2.8	43.4	17.4	8.7
	4.0	62.1	24.8	12.4
Angle of View (H)	106.7°			
Angle of View (V)	57.1°			
Angle of View (O)	115.7°			
Adjustment angle	Pan: 0° ~ 360°		Tilt: 0° ~ 90°	
Shutter	Auto/Manual, 1 ~ 1/100000s			
Minimum Illumination	Colour: 0.02Lux (F2.1, AGC ON) 0Lux with IR on			
Digital noise reduction	2D/3D DNR			
Day/Night	IR-cut filter with auto switch (ICR)			
S/N	>52dB			
IR Range	Up to 30m (98ft) IR range			
Defog	Digital Defog			
WDR	DWDR			

Audio	
Audio Compression	G.711
Suppression	Supported
Sampling Rate	8KHZ
Video	
Video Compression	Ultra 265, H.265, H.264
H.264 code profile	Baseline profile, Main profile, High profile
Frame Rate	Main Stream: 1080P (1920*1080), Max 25fps; 720P (1280*720), Max 25fps; Sub Stream: D1 (720*576), Max 25fps; 640*360, Max 25fps; 2CIF(704*288), Max 25fps; CIF(352*288), Max 25fps;
HLC	Supported
BLC	Supported
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Network	
Protocols	IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP, RTMP
Compatible Integration	ONVIF (Profile S, Profile T), API
Interface	
Network	10/100M Base-TX Ethernet
Built-in Mic	Supported
General	
Power	DC 12V±25%, PoE
	Power consumption: Max 3.5W
Dimensions (L x W x H)	144 x 60 x 65mm (5.6" x 2.4" x 2.6")
Weight	0.17kg (0.37lb)
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	4KV
Ingress Protection	IP67
Reset Button	N/A