eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

DAHUA

IPC-HD4140X-3D

Kod: 00-00002156 · Kamera



DAHUA - IPC-HD4140X-3D 1.3MP DUAL-LENS PEOPLE COUNTING AI NETWORK KAMERA, 1.3MP sensor və 3D texnologiyası ilə insan axınını yüksək dəqiqliklə sayır. Mağaza, ticarət mərkəzi və ofis girişlərində real-time analitika, statistik hesabatlar və inteqrasiya dəstəyi ilə müasir təhlükəsizlik və idarəetmə həlli təqdim edir.

Texniki göstəricilər

IP Növ	**2 MP** Meqapixel
Mic Mikrofon	**Sabit** Obyektiv
2.8mm Fokus	**İR** İşıqlandırma
20 m İşıqlandırma məsafəsi	**Metal** Material
MicroSD Yaddaş	**Indoor** İş mühiti

Ətraflı məlumat

Camera					
Image Sensor	Two 1/3”1.3Megapixel progressive scan CMOS				
Effective Pixels	1028(H)x960(V)				
RAM/ROM	512MB/128MB				
Scanning System	Progressive				
Minimum Illumination	0.003Lux/F2.2 (Color,1/3s,30IRE) 0.02Lux/F2.2 (Color,1/30s,30IRE) 0.005Lux/F2.2 (B/W,1/3s,30IRE) 0.02Lux/F2.2 (B/W,1/30s,30IRE)				
S/N Ratio	More than 50dB				
IR Distance	N/A				
IR On/Off Control	N/A				
IR LEDs	N/A				
Lens					
Lens Type	Fixed				
Mount Type	Board-in				
Focal Length	2.1mm (2.8mm)				
Max. Aperture	F2.2				
Angle of View	H: 109.5° (89°), V: 84.3° (64°)				
Optical Zoom	N/A				
Focus Control	Fixed				
Close Focus Distance	0.3m (0.98ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.1 mm	24m(79ft)	10m(33ft)	4.8m(15.7ft)	2.4m(7.9ft)
	2.8 mm	35m(115ft)	14m(46ft)	7m(23ft)	3.5m(11.5ft)
Pan/Tilt/Rotation					

Pan/Tilt/Rotation Range	N/A
Artificial Intelligence	
People Counting	Line crossing people counting, Region people counting, Height filter, Loitering filter
General Intelligence	
Event Trigger	Motion detection, Video tampering, Scene changing, Network disconnection, Ip address conflict, Illegal access, Storage anomaly
General Intelligence	N/A
Video	
Compression	H.265/H.264/H.264H/H.264B/MJPEG(Sub Stream)
Smart Codec	Support H.265+/H.264+
Streaming Capability	3 Streams
Resolution	1.3M(1280x960)/ 720P(1280x720)/ D1(704×576/704x480)/ VGA(640x480)
Frame Rate	Main Stream: 1.3MP (1~25/30fps)
	Sub Stream 1: D1 (1 ~ 25/30fps)
	Sub Stream 2: 720P (1~25/30fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.264: 1280~ 6144Kbps H.265: 512~ 3072Kbps
Day/Night	Electronic
BLC Mode	BLC / HLC /DWDR
White Balance	Auto/Manual
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detection	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)

Electronic Image Stabilization (EIS)	N/A
Smart IR	N/A
Defog	N/A
Digital Zoom	16x
Flip	N/A
Mirror	N/A
Privacy Masking	Off / On (4 Area, Rectangle)
Audio	
Compression	G.711a/ G.711Mu/ AAC/ G.726
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	HTTP;HTTPs;TCP;ARP;RTSP;RTP;UDP;RTCP;SMTP; FTP;DHCP;DNS;DDNS;PPPOE;IPv4/v6;QoS;UPnP; NTP;Bonjour;IEEE 802.1x;Multicast;ICMP;IGMP;SNMP;TLS
Interoperability	ONVIF Profile S&G, API
Streaming Method	Unicast / Multicast
Max. User Access	10 Users/20 Users
Edge Storage	NAS Local PC for instant recording Mirco SD card 128GB
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	Smart PSS, DSS, DMSS
Smart Phone	IOS, Android
Certifications	
Certifications	CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B

Interface	
Video Interface	N/A
Audio Interface	Built-in Mic
RS485	1 port
Alarm	1 channel In: 5mA 5VDC 1 channel Out: 300mA 12VDC
Electrical	
Power Supply	DC12V, PoE (IEEE 802.3af)(Class 0)
Power Consumption	DC12V: 3.6W 4.6W(People Counting on) PoE: 4.2W 5.3W((People Counting on))
Environmental	
Operating Conditions	-10° C ~ +45° C (14° F ~ +113° F) / Less than 95% RH
Storage Conditions	-10° C ~ +45° C (14° F ~ +113° F) / Less than 95% RH
Ingress Protection	IP54
Vandal Resistance	N/A
Construction	
Casing	Metal
Dimensions	162.1mmx76mmx37.8mm (6.38"x2.99"x1.49")
Net Weight	0.3kg (0.66lb)
Gross Weight	0.46kg (1.01lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az