

# IPC-HDW1230SP-0280B

Dahua IPC-HDW1230SP-0280B 2 MP IP kamera; Piksel 1920×1080; IR işıqlandırma - 30 m; F2.8 mm; Bucaq-101°-33.5°;



Model	IPC-HDW1230SP-0280B
Brend	Dahua
Növ	IP
Meqapixel	2 MP
İşıqlandırma məsafəsi	30 m
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
Qoruma	IP67
Material	Plastik

## Specification

Standard:	TCP/IP
Sensor:	1/2.8 " Progressive Scan CMOS
Scanning system:	Progressive
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens:	2.8 mm
View angle:	<ul style="list-style-type: none"><li>• 102 ° (manufacturer data)</li><li>• 98 ° (our tests result)</li></ul>
Range of IR illumination:	30 m
Memory card slot:	—
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	—
Audio:	—
Main stream frame rate:	25 fps @ 1080p
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, SMTP, FTP, DHCP, DNS, NTP, Multicast
WEB Server:	Built-in
Max. number of on-line users:	20

<b>ONVIF:</b>	20.06
<b>Main features:</b>	<ul style="list-style-type: none"><li>• D-WDR - Wide Dynamic Range</li><li>• 3D-DNR - Digital Noise Reduction</li><li>• ROI - improve the quality of selected parts of image</li><li>• BLC - Back Light Compensation</li><li>• HLC - High Light Compensation (spot)</li><li>• ICR - Movable InfraRed filter</li><li>• AGC - Automatic Gain Control</li><li>• Auto White Balance</li><li>• Mirror - Mirror image</li><li>• Configurable Privacy Zones</li><li>• Motion Detection</li></ul>
<b>Port ONVIF:</b>	80
<b>Power supply:</b>	<ul style="list-style-type: none"><li>• PoE (802.3af),</li><li>• 12 V DC / 360 mA</li></ul>
<b>Power consumption:</b>	≤ 2.3 W @ 12 V DC ≤ 4.4 W @ PoE (802.3af)
<b>Housing:</b>	Dome - Metal + Plastic
<b>Color:</b>	White
<b>"Index of Protection":</b>	IP67
<b>Operation temp:</b>	-40 °C ... 60 °C
<b>Dimensions:</b>	Ø 108 x 85 mm
<b>Weight:</b>	0.27 kg