

IPC-HDW1230SP-0280B

Dahua IPC-HDW1230SP-0280B 2 MP IP kamera; Piksel 1920×1080; IR işıqlandırma - 30 m; F2.8 mm; Bucaq-101°-33.5°;



Model	IPC-HDW1230SP-0280B
Brend	Dahua
Növ	IP
Meqapixel	2 MP
İşıqlandırma məsafəsi	30 m
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
Qoruma	IP67
Material	Plastik

Specification

Standard:	TCP/IP
Sensor:	1/2.8 " Progressive Scan CMOS
Scanning system:	Progressive
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens:	2.8 mm
View angle:	<ul style="list-style-type: none">• 102 ° (manufacturer data)• 98 ° (our tests result)
Range of IR illumination:	30 m
Memory card slot:	—
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	—
Audio:	—
Main stream frame rate:	25 fps @ 1080p
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, SMTP, FTP, DHCP, DNS, NTP, Multicast
WEB Server:	Built-in
Max. number of on-line users:	20
ONVIF:	20.06

Main features:	<ul style="list-style-type: none">• D-WDR - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• ROI - improve the quality of selected parts of image• BLC - Back Light Compensation• HLC - High Light Compensation (spot)• ICR - Movable InfraRed filter• AGC - Automatic Gain Control• Auto White Balance• Mirror - Mirror image• Configurable Privacy Zones• Motion Detection
Port ONVIF:	80
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 360 mA
Power consumption:	≤ 2.3 W @ 12 V DC ≤ 4.4 W @ PoE (802.3af)
Housing:	Dome - Metal + Plastic
Color:	White
"Index of Protection":	IP67
Operation temp:	-40 °C ... 60 °C
Dimensions:	Ø 108 x 85 mm
Weight:	0.27 kg