

IPC-HDW1230T1P-ZS-S5-QH

Dahua IPC-HDW1230T1P-ZS-S5-QH 2 MP IP zoom kamera; Piksel 1920×1080; IR işıqlandırma - 40 m; F2.8 - 12 mm; Bucaq-101°-33.5°;

Model	IPC-HDW1230T1P-ZS-S5-QH
Brend	Dahua
Qoruma	IP67
Növ	IP
Meqapixel	2 MP
Obyektiv	Motorized
Fokus	2.7 - 13.5mm
İşıqlandırma	İR
İşıqlandırma məsafəsi	40 m
Material	Metal
İş mühiti	Indoor



Specification

Camera	
Image Sensor	1/2.8" CMOS
Max. Resolution	1920 (H) × 1080 (V)
ROM	16 MB
RAM	128 MB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 s-1/100,000 s
Min. Illumination	0.005 Lux@F1.5 (Color, 30 IRE) 0.0005 Lux@F1.5 (B/W, 30 IRE) 0 Lux (Illuminator on)
S/N Ratio	> 56 dB
Illumination Distance	40 m (131.23 ft) (IR)
Illuminator On/Off Control	Auto; Manual
Illuminator Number	2 (IR)
Pan/Tilt/Rotation Range	Pan: 0°-355° Tilt: 0°-78° Rotation: 0°-360°
Lens	
Lens Type	Motorized vari-focal
Lens Mount	φ14
Focal Length	2.8 mm-12 mm
Max. Aperture	F1.5

Field of View	Horizontal: 101°-33.5°; Vertical: 52.5°-19°; Diagonal: 125°-38.5°				
Iris Control	Fixed				
Close Focus Distance	1.2 m (3.94 ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	W	48 m (157.48 ft)	19 m (62.34 ft)	10 m (32.81 ft)	5m (16.40 ft)
	T	131 m (429.79 ft)	52 m (170.60 ft)	26 m (85.30 ft)	13m (42.65 ft)
Video					
Video Compression	H.265; H.264; H.264B; MJPEG (Only supported by the sub stream)				
Smart Codec	Smart H.265+; Smart H.264+				
Video Frame Rate	Main stream:1920 × 1080@1-25/30 fps Sub stream: 704 × 576@1-25 fps/704 × 480@1-30 fps *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.				
Bit Rate Control	CBR/VBR				
Video Bit Rate	H.264: 32 kbps-6144 kbps H.265: 12 kbps-6144 kbps				
Day/Night	Auto(ICR)/Color/B/W				
BLC	Yes				
HLC	Yes				
WDR	DWDR				
Scene Self-adaptation (SSA)	NA				
White Balance	Auto; natural; street lamp; outdoor; manual; regional custom				
Gain Control	Auto; manual				
Noise Reduction	3D NR				
Motion Detection	OFF/ON (4 areas, rectangular)				
Region of Interest (RoI)	Yes (4 areas)				
Image Stabilization	NA				
Smart Illumination	Yes				
Defog	NA				
Image Rotation	0°/90°/180°/270° (Support 90°/270° with 1080p resolution and lower)				
Mirror	Yes				
Privacy Masking	4 areas				
Alarm					
Alarm Event	No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception; defocus detection				
Network					
Network Port	RJ-45 (10/100 Base-T)				
SDK and API	Yes				
Cyber Security	Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTPS; trusted boot; trusted execution; trusted upgrade				
Network Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; SMTP; FTP; DHCP; DNS; NTP; Multicast; DDNS				
Interoperability	ONVIF (Profile S/Profile T); CGI; P2P; Milestone				
User/Host	6				
Storage	FTP; Micro SD card (Support max. 256 G)				

Browser	IE Chrome Firefox
Management Software	Smart PSS; DSS; DMSS
Mobile Client	IOS; Android
Certification	
Certifications	CE-LVD: EN60950-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B
Power	
Power Supply	12 V DC; PoE
Power Consumption	Basic: 1.6 W (12 V DC); 2.4 W (PoE) Max. (H.265+ICR+IR intensity): 3.9 W (12 V DC); 5 W (PoE)
Environment	
Operating Temperature	-30 °C to +60 °C (-22 °F to 140 °F)
Operating Humidity	≤95%
Protection	IP67
Structure	
Casing	Metal + plastic
Product Dimensions	108.8 mm × Ø122 mm (4.28" × Ø4.80")
Net Weight	0.44 kg (0.97 lb)
Gross Weight	0.63 kg (1.39 lb)