eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

DAHUA

IPC-HDW1239VP-A-IL-0280B-S5-QH2

Kod: 00-00004961 · Kamera



DAHUA IPC-HDW1239VP-A-IL-0280B-S5-QH2 2MP FULL-COLOR NETWORK KAMERA

Texniki göstəricilər

IP Növ	**2 MP** Meqapixel
LED İşıqlandırma	**Mic** Mikrofon
Sabit Obyektiv	**2.8mm** Fokus
30 m İşıqlandırma məsafəsi	**IP67** Qoruma
Plastik Material	**Indoor** İş mühiti

Ətraflı məlumat

Camera	
Matrix	1/2.8" CMOS, 2 MP
Effective pixels (H×V)	1920×1080
ROM	128 MB
RAM	128 MB
Scan	Progressive
Electronic shutter	Auto, Manual (1/3 sec ~ 1/100000 sec)
Sensitivity	0.005Lux (Color, F1.6, 30 IRE) 0.0005Lux (B/W, F1.6, 30 IRE) 0Lux (Backlight)
Signal/noise	>56 dB
Backlight range	≤30m(IR illumination) ≤30m(LED illumination)
Backlight control	Auto, manual
Backlight module	1 IR diode 1 warm spectrum LED
Axes adjustment	Pan: 0° ~ 360° Tilt: 0° ~ 78° Rotate: 0° ~ 360°
Lens	
Type	Fixed
Mounting type	Built-in (M12)
Focal length	2.8mm / 3.6mm
Diaphragm	F1.6

Field of view	Horizontal: 104° / 88° Vertical: 55° / 44° Diagonal: 124° / 105°				
Aperture control	No				
Minimum focusing distance	0.8 m / 1.3 m				
Distance O.N.R.I. (DORI)	Focal length	Detection	Observation	Recognition	Identification
	2.8 mm	44.1 m	17.7 m	8.8 m	4.4 m
	3.6 mm	58.9 m	23.6 m	11.8 m	5.9 m
Professional video analytics					
People Detection	Supports classification and accurate detection of people				
Intelligent search	Works with intelligent IP DVRs to perform precise intelligent search, event retrieval, and event-to-video linking				
Video					
Video compression	H.265, H.264 (Base, Main, High), MJPEG (on additional stream)				
Optimized codecs	H.265+, H.264+				
Frame rate	Main Stream: 1920×1080 @ 1 fps ~ 25 fps Sub Stream 1: 704×576 @ 1 fps ~ 25 fps *The values shown for each video stream are maximum; when transmitting multiple video streams simultaneously, their frame rate will decrease depending on available computing resources.				
Number of threads	2				
Frame formats	1080p (1920×1080), 960p (1280×960), 720p (1280×720), D1 (704×576), VGA (640×480), CIF (352×288)				
Video Stream Control	CBR, VBR				

Video stream size	H.264: 32Kbps ~ 4096Kbps H.265: 12Kbps ~ 4096Kbps
Day/Night Mode	Switching IR filter (auto, manual)
Backlight compensation	BLC, HLC
Wide dynamic range	DWDR
White balance	Auto, natural, street lighting, street, manual, zonal
Signal amplification	Auto, manual
Noise reduction	3D DNR
Motion detection	Yes (4 zones)
Regions of Interest (RoI)	Yes (4 zones)
Intelligent backlight	Yes
Rotate image	90°, 180°, 270°
Mirroring	Yes
Private areas	Yes (4 zones)
Audio	
Built-in microphone	Yes
Audio compression	G.711a, G.711mu, G.726, PCM
Signaling	
Disturbing developments	Network failure, IP conflict, unauthorized access, motion, lens tampering, audio detection alarm, SMD(people) alarm, security error
Net	
Ethernet	RJ-45 (10 Mbit/s, 100 Mbit/s)

Protocols	ARP, DDNS, DHCP, DNS, FTP, HTTP, ICMP, IGMP, IPv4, IPv6, Multicast, NTP, RTCP, RTP, RTSP, SMTP, TCP, UDP
Safety	Configuration encryption, trusted execution, digest authentication, security logs, HTTPS, trusted update, WSSE, trusted boot, account lockout, X.509 certificate generation and import, video encryption
Compatibility	ONVIF(S,T),CGI
SDK and API	Yes
Maximum number of connections	6 (total flow 24 Mbps)
Peripheral storage	FTP
Web clients	Internet Explorer, Google Chrome, FireFox
Clients	Smart PSS Lite, DSS, DMSS
Mobile clients	iOS, Android
Certification	
Certificates	EN62368-1 (EU Low Voltage Directive) 2014/30/EU (EU EMC)
Power supply	
Nutrition	12V (DC), PoE (802.3af)
Power consumption	Basic: 1.8 W (12 V), 2.3 W (PoE) Maximum (H.265, video analytics, WDR, backlight): 4.5 W (12 V), 5.6 W (PoE)
terms of Use	
Operating temperature	-40°C ~ +60°C
Working humidity	≤95%

Storage temperature	-40°C ~ +60°C
Storage humidity	≤95%
Protection	IP67
Physical parameters	
Body material	Metal, plastic
Dimensions	Ø 109.9 mm × 100.9 mm
Weight	Net: 0.33 kg Gross: 0.45 kg

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az