

IPC-HDW1431T1P-S4

DAHUA -IPC-HDW1431T1P-S4(2,8mm) - 4MP



Specifications

Model	IPC-HDW1431T1P-S4
Brand	Dahua
Material	Plastik
Qoruma	IP67
Növ	IP
Meqapixel	4 MP
??qland?rma m?saf?si	30 m
Obyektiv	Sabit
Fokus	2.8mm
??qland?rma	İR
Yadda?	MicroSD
?? mühiti	Indoor

KEY FEATURES

Camera

Image 1/3" 4Megapixel progressive CMOS

Sensor

Max. 2688 (H) x1520 (V)

Resolution

ROM 128 MB

RAM 128 MB

Scanning Progressive

System

Electronic Auto/Manual 1/3 s-1/100000 s

Shutter

Speed

S/N Ratio > 56 dB

Min. 0.03 Lux @ F2.0

Illumination

Illumination 30 m (98.4 ft)

Distance

Illuminator Auto/Manual

On/Off

Control

Illuminator 1(IR LED)

Number

Pan/Tilt/Rotation 0°-355°

Range Tilt: 0°-78°

Rotation: 0°-360°

Lens

Lens Type Fixed-focal

Mount Type M12

Focal Length 2.8 mm

3.6 mm

Max. F2.0

Aperture

Field of View 2.8 mm:

Horizontal: 93°

Vertical: 53°

Diagonal: 111°

3.6 mm:

Horizontal: 81°

Vertical: 44°

Diagonal: 95°

Iris Type Fixed

Close Focus 2.8 mm: 0.8 m (2.6 ft)

Distance 3.6 mm: 1.4 m (4.6 ft)

DORI Lens Detect Observe Recognize Identify

Distance

2.8mm
50.0 22.4 m 11.2 m 15.1 m
m (73.5 ft) (36.7 ft) (18.4 ft)
(183.7
ft)

3.6mm
80.0 32.0 m 16.0 m 8.0 m
m (105.0 ft) (52.5 ft) (26.2 ft)
(262.5
ft)

Video

Video Compression H.265; H.264; H.264B; MJPEG(only supported by sub stream)

Smart Codec Smart H.265+/ Smart H.264+

Video Frame Main Stream:

Rate 2688 × 1520 (1 fps–20 fps)
2560 × 1440 (1 fps–25/30 fps)
Sub Stream:
704 × 576 (1 fps–20/25 fps)
704 × 480 (1 fps–20/30 fps)

Stream 2 streams

Capability

Resolution 2688 × 1520 (2688 × 1520); 2560 × 1440 (2560 × 1440); 2304 × 1296 (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)

Bit Rate CBR; VBR

Control

Video Bit Rate H.264: 32 kbps–6144 kbps

H.265: 12 kbps–6144 kbps

Day/Night Auto(ICR)/Color/B/W

BLC Yes

HLC Yes

WDR 120 dB

White Balance Auto/natural/street lamp/outdoor/manual/regional custom

Gain Control

Manual/Auto

Noise Reduction 3D NR

Motion Detection

OFF/ON (4 areas, rectangular)

Region of Interest(Roi)

Yes (4 areas)

Smart Illumination

Yes

Image Rotation

0°/90°/180°/270° (Support 90°/270° with 2688 × 1520 resolution and lower.)

Mirror

Yes

Privacy Masking 4 areas

Alarm

Alarm Event

Network disconnection; IP conflict; motion detection; video tampering; illegal access; voltage detection; security exception