

# IPC-HFW1230S1P-S5-0360B

Dahua IPC-HFW1230S1P-S5-0360B 2 MP IP kamera; Piksel 1920×1080; IR işıqlandırma - 30 m; F3.6 mm; Bucaq-102°;

Model	IPC-HFW1230S1P-S5-0360B
Brend	Dahua
Növ	IP
Meqapixel	2 MP
İşıqlandırma məsafəsi	30 m
Obyektiv	Sabit
Fokus	3.6
İşıqlandırma	İR
Qoruma	IP67
Material	Plastik



## Specification

Camera	
Image Sensor	1/2.8" CMOS
Max. Resolution	1920 (H) × 1080 (V)
ROM	16 MB
RAM	64 MB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 s-1/100000 s
Min. Illumination	0.01 Lux @F2.0
S/N Ratio	>56 dB
Illumination Distance	30 m (98.4 ft)
Illuminator On/Off Control	Auto/Manual
Illuminator Number	1 (IR LED)
Pan/Tilt/Rotation Range	Pan: 0° to 360° Tilt: 0° to 90° Rotation: 0° to 360°
Lens	
Lens Type	Fixed-focal

Lens Mount	M12				
Focal Length	2.8 mm; 3.6 mm				
Max. Aperture	2.8 mm: F2.0 3.6 mm: F2.0				
Field of View	2.8 mm: Horizontal: 102°; Vertical: 54°; Diagonal: 120° 3.6 mm: Horizontal: 84°; Vertical: 45°; Diagonal: 100°				
Iris Control	Fixed				
Close Focus Distance	2.8 mm: 0.5 m (1.6 ft) 3.6 mm: 0.8 m (2.6 ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	38.6 m (126.6 ft)	15.4 m (50.5 ft)	7.7 m (25.3 ft)	3.9 m (12.8 ft)
	3.6 mm	49.7 m (163.1 ft)	19.9 m (65.3 ft)	9.9 m (32.5 ft)	5.0 m (16.4 ft)
Video					
Video Compression	H.265; H.264; H.264B; MJPEG (only supported by the sub stream)				
Smart Codec	Smart H.265+/Smart H.264+				
Video Frame Rate	Main Stream: 1920 × 1080 (1 fps–25/30 fps) Sub stream: 704 × 576 (1 fps–25 fps) 704 × 480 (1 fps–30 fps)				
Stream Capability	2 streams				
Resolution	1080p (1920 × 1080); 1.3M(1280 × 960);720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)				
Bit Rate Control	CBR/VBR				
Video Bit Rate	H.264: 32 kbps–6144 kbps H.265: 12 kbps–6400 kbps				
Day/Night	Auto (ICR)/Color/B/W				
BLC	Yes				
HLC	Yes				
WDR	DWDR				
White Balance	Auto/natural/street lamp/outdoor/manual/regional custom				
Gain Control	Auto/Manual				
Noise Reduction	3D NR				
Motion Detection	OFF/ON (4 areas, rectangular)				
Region of Interest (RoI)	Yes (4 areas)				
Smart Illumination	Yes				
Image Rotation	0°/90°/180°/270° (Support 90°/270° with 1080p resolution and lower)				
Mirror	Yes				
Privacy Masking	4 areas				

<b>Alarm</b>	
<b>Alarm Event</b>	Network disconnection; IP conflict; illegal access; motion detection; video tampering; safety exception
<b>Network</b>	
<b>Network</b>	RJ-45 (10/100 Base-T)
<b>SDK and API</b>	Yes
<b>Cyber Security</b>	Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTPS; trusted boot; trusted execution; trusted upgrade
<b>Network Protocol</b>	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; SMTP; FTP; DHCP; DNS; NTP; Multicast
<b>Interoperability</b>	ONVIF (Profile S/Profile T); CGI; P2P; Genetec
<b>User/Host</b>	6 (Total bandwidth: 36 M)
<b>Storage</b>	FTP
<b>Browser</b>	IE Chrome Firefox
<b>Management Software</b>	Smart PSS; DSS; DMSS
<b>Mobile Client</b>	IOS; Android
<b>Certification</b>	
<b>Certifications</b>	CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B
<b>Power</b>	
<b>Power Supply</b>	12V DC/PoE (802.3af)
<b>Power Consumption</b>	Basic power consumption: 1.4W (12V DC); 2.2W (PoE) Max. power consumption (ICR + H.265+IR intensity): 3.3W (12V DC); 4.3W (PoE)
<b>Environment</b>	
<b>Operating Conditions</b>	-40°C to +60°C (-40°F to +140°F)/less than ≤ 95%
<b>Storage Temperature</b>	-40°C to +60°C (-40°F to +140°F)
<b>Protection</b>	IP67
<b>Structure</b>	
<b>Casing</b>	Metal + plastic
<b>Product Dimensions</b>	162.6 mm × Φ70 mm (6.4" × Φ2.8")
<b>Net Weight</b>	0.22 kg (0.4 lb)
<b>Gross Weight</b>	0.34 kg (0.7 lb)